

# SCIENTIFIC AMERICAN

[Entered at the Post Office of New York, N. Y., as Second Class Matter. Copyrighted, 1890, by Munn & Co.]

A WEEKLY JOURNAL OF PRACTICAL INFORMATION, ART, SCIENCE, MECHANICS, CHEMISTRY, AND MANUFACTURES.

Vol. LXII.—No. 18.  
ESTABLISHED 1845.

NEW YORK, MAY 3, 1890.

\$3.00 A YEAR.  
WEEKLY.

## THE WESTINGHOUSE INTERLOCKING SWITCH AND SIGNAL SYSTEM.

Some weeks ago we illustrated the electro-pneumatic block system of train signaling. In our present issue we present our readers with illustrations of some of the salient points of the Westinghouse interlocking switch and signal mechanism for use in train yards. It includes three operating agencies, electricity, pneumatic pressure, and hydraulic pressure. The work of throwing switches and of setting signals at safety is done by pneumatic pressure. The valves for regulating its action on signals are worked by electricity exactly as in the block system already described. The valves for regulating its action on switches are moved by hydraulic pressure.

Referring to the perspective view of the switch board, it will be seen to be a case upon whose front are two rows of handles. These handles, when moved by the operative, turn through an arc of a circle long vulcanite-covered spindles that run to the back of the case. These spindles are numbered in pairs; of similar numbers, those to the left are rotated by the lower handles, those to the right by the upper handles. On the rear end of each spindle is a quadrant with locking detent, worked electrically. The upper row of handles operates the switches; the lower row operates the signals.

At the rear of each switch spindle, that is to say of every second one, is a three-way cock attached directly to the spindle, and therefore turned by the upper handle appertaining to the spindle in question. This cock is a part of the hydraulic system. Turned to the right, it operates by hydraulic pipe connections a valve in the neighborhood of a switch which may be a mile or more distant. The operation of this valve, which is connected to pneumatic pipes, admits compressed air to the actuating cylinder and piston, and throws the switch in one or the other direction. The switch-throwing mechanism will be described later on.

When a current of electricity is passed through the actuating magnet of the signal-moving mechanism, Fig. 3, which also may be at any distance, it opens a pneumatic valve, admitting air to the signal-actuating cylinder, placed on the semaphore post. The piston is forced outward and the semaphores are depressed to the safety position. This current is sent through the switch board, when the handles are set in proper position therefor. On each of the vulcanite-coated spindles are placed strips of platinum, and between the spindles are pairs of contact springs. These, with their




Fig. 1.—AUTOMATIC SWITCH-OPERATING MECHANISM.

connections, can be arranged in any way whatever to suit the conditions of the case. The circuit, including the semaphore magnet, is completed through one or more of these spindle connections. Hence the setting of any given semaphore at safety may be made to depend upon one or more switch movements, as necessary. After the switch handles in its series are properly set, they complete their part of the circuit by means of the platinum strips and springs. Then the final turn of the signal handle moves its spindle into position and the circuit is completed, and the semaphore descends to "safety." When the switches are to be changed, the signal circuit has first to be broken. This permits the

which K is the rack and A is the pinion. The air admitted by one of the pipes, *d d*, forces the pistons in one or the other direction, regulated by the D-valve, thus turning the pinion. As the pinion turns it carries around with it an arm attached to its spindle, *a*. In its revolution through about three-quarters of a circle the pinion has to successively perform the following operations: 1. To withdraw the locking bolt, H, from the hole in the locking bar, N; 2, throw the switch, by moving the rod, M; 3, return the locking bolt, H, to the other hole in the locking bar, N.

Referring to the sectional view, H is the locking bolt, N the locking bar, and M is the switch rod. If air is

admitted to the right hand end of the cylinder, the other end communicating with the open air, the pistons will move to the left. The movement of the pinion may be divided into three phases, indicated by the dotted lines. Moving from 0 to 1 it withdraws the lock bolt, but practically does not move the switch bar, or at least only back and forth through the versed sine of the arc described by the crank pin between 0 and 1. From 1 to 2 the relations are changed; here the switch rod is moved through a longer distance, corresponding to the chord of the arc, 1-2, throwing the switch, while the lock bolt is

(Continued on page 279.)




Fig. 2.—ELECTRO-PNEUMATIC INTERLOCKING SWITCH AND SIGNAL STATION AT PITTSBURG, PA.

Scientific American.

ESTABLISHED 1845.

MUNN & CO., Editors and Proprietors.

PUBLISHED WEEKLY AT

No. 361 BROADWAY, NEW YORK.

O. D. MUNN.

A. E. BEACH.

TERMS FOR THE SCIENTIFIC AMERICAN.

One copy, one year, for the U. S., Canada or Mexico. \$3 00
One copy, six months, for the U. S., Canada or Mexico. 1 50
One copy, one year, to any foreign country belonging to Postal Union. 4 50

The Scientific American Supplement

is a distinct paper from the SCIENTIFIC AMERICAN. THE SUPPLEMENT is issued weekly. Every number contains 16 octavo pages, uniform in size with SCIENTIFIC AMERICAN. Terms of subscription for SUPPLEMENT, \$5.00 a year, for U. S., Canada or Mexico. \$6.00 a year to foreign countries belonging to the Postal Union. Single copies, 10 cents. Sold by all newsdealers throughout the country. See prospectus last page.

Building Edition.

THE ARCHITECTS and BUILDERS EDITION OF THE SCIENTIFIC AMERICAN is a large and splendid illustrated periodical, issued monthly, containing floor plans, perspective views, and sheets of constructive details, pertaining to modern architecture. Each number is illustrated with beautiful plates, showing desirable dwellings, public buildings and architectural work in great variety. To builders and all who contemplate building this work is invaluable. Has the largest circulation of any architectural publication in the world.

Single copies 25 cents. By mail, to any part of the United States, Canada or Mexico, \$2.50 a year. To foreign Postal Union countries, \$3.00 a year. Combined rate for BUILDING EDITION with SCIENTIFIC AMERICAN, \$8.00 a year; combined rate for BUILDING EDITION, SCIENTIFIC AMERICAN and SUPPLEMENT, \$9.00 a year. To foreign countries, \$11.50 a year.

Spanish Edition of the Scientific American.

LA AMERICA CIENTIFICA E INDUSTRIAL (Spanish trade edition of the SCIENTIFIC AMERICAN) is published monthly, uniform in size and typography with the SCIENTIFIC AMERICAN. Every number of La America is profusely illustrated. It is the finest scientific and industrial trade paper printed in the Spanish language. It circulates throughout Cuba, the West Indies, Mexico, Central and South America, Spain and Spanish possessions—wherever the Spanish language is spoken. \$3.00 a year, post paid to any part of the world. Single copies 25 cents. See prospectus.

MUNN & CO., Publishers, 361 Broadway, New York.

The safest way to remit is by postal order, express money order, draft or bank check. Make all remittances payable to order of MUNN & CO.

NEW YORK, SATURDAY, MAY 3, 1890.

Contents.

(Illustrated articles are marked with an asterisk.)

Table listing various articles such as Acid, sulphuric, New Zealand, Bed, animal, Stevenson's, Bill, patent, questionable, Bridge, Hudson River, Chinaman, persecuted, Epidemic, pension, Fair, world's, in Chicago, Gas, waste of, Gun, a heavy, Guns, great, Russian, Indigo, synthetic, Invention, what, Irene, German armorclad, Knife, automatic, Wilzin, Lighter, shaft, Stevenson's, Longevity in Norway, Machine, grinding, Kidley's, Medal, W. R. Brooks, Plant, hoisting, elaborate, Plating, cobalt, hints on, Pipes, steel, Powder, a smokeless, Pump, vacuum, new, Register, time, Tiffany's, Salesman, traveling, Sand, unstable, School of Industrial Art, Sling, hay, Unterbrink's, Stamp, time, automatic, Substances, explosive, Switches, interlocking, Westinghouse, house, Tobacco, Trade, salmon, German, Universities, American, Valve, steam engine, Gehring's, Water, action of, Well, oil, Southbury, Conn., Windlass, well, Bridges, Wires, elec. light, in Montevideo

TABLE OF CONTENTS OF SCIENTIFIC AMERICAN SUPPLEMENT No. 748.

For the Week Ending May 3, 1890.

Price 10 cents. For sale by all newsdealers.

Table listing detailed contents of the supplement, including sections like I. AGRICULTURE, II. BIOGRAPHY, III. CIVIL ENGINEERING, IV. ELECTRICITY, V. MINING ENGINEERING, VI. MISCELLANEOUS, VII. ORDNANCE, VIII. PHARMACY, IX. PHOTOGRAPHY, X. PHYSICS, XI. TECHNOLOGY.

A QUESTIONABLE PATENT BILL.

Many bills have from time to time been introduced in Congress, but not as yet passed, having for their object to crush the patentees of new inventions and benefit pirates and infringers, depriving patentees of the means of enforcing their patents and securing damages in the courts. It is, therefore, refreshing now to find a bill introduced in both branches of the national legislature which, ostensibly, is intended to protect the inventor.

It is common for wealthy corporations and others, who find infringements of patents to be profitable, to band together in supplying money and lawyers for their mutual defense. If, for example, John Doe, the inventor and patentee, finds several different parties infringing his rights, his proper course is to bring suit against one of the parties first and obtain the judgment of the court; after which, if the decision is favorable, he can proceed against the other infringers more economically and with greater expedition than if all had been separately attacked in the first instance. By the formation of a ring or combine on the part of the infringers they bring their united efforts to bear whenever one of their number is sued, and endeavor in every possible way to worry, harass, and defeat the inventor. The bill now before Congress (S. 3347) is entitled: "A bill to forbid maintenance and oppression in suits brought upon letters patent." It provides "That whenever it shall appear in any suit concerning letters patent of the United States that the defense of the suit is interfered with or maintained by a combination of individuals or by a combination of corporations, or both, or by any attorney or officer of such combination not lawful defendants thereto, originally or by intervention, any such interference or maintenance is hereby declared to be a public offense; and the attorney of the United States for the district where such action is pending shall, upon the affidavit of the plaintiff, supported by the affidavits of two other persons filed in the court where the suit is pending, naming such combination of individuals, or combination of corporations, or both, summarily present the names of all parties so complained of to a grand jury for indictment, and upon a bill of indictment found said attorney shall criminally prosecute each and every one indicted, and upon trial and conviction the judge of the court shall impose a fine of not less than two nor more than ten thousand dollars upon each individual or corporation offender; and in the case of any association or trust composed of individuals or corporation offenders, or both, the said United States attorney shall proceed in equity immediately after such conviction to dissolve such association or trust and to confiscate its property to the use of the United States, and circuit courts of the United States shall have original jurisdiction of this offense."

There is another aspect of the subject which makes it questionable whether this proposed law ought to pass: for while it might tend to assist the honest and humble inventor plaintiff, it might also be used with disastrous effect by a rich and powerful corporation plaintiff for the purpose of distressing and compelling the surrender of innocent defendants. For instance, it might be asked why such powerful and unconscionable monopolies as the Western Union Telegraph Company or the Bell Telephone Company should need the help of a special act of Congress like this, to prevent other people and other corporations from uniting against either of them for purposes of legitimate mutual defense.

Why should the law make it a crime for a poor defendant to call in aid for his defense while it regards as innocent the powerful plaintiff who does the same thing in the prosecution? Under this law the plaintiff is at liberty to make as many combinations with individuals and corporations as he chooses, and to use this combined strength against the defendant. This law, without any regard to the merits of the cause, makes saints of plaintiffs and sinners of defendants.

A New Vacuum Pump.

An exhibition of the vacuum pump of Mr. Adolph Berenberg, of Somerville, Mass., was given recently in Boston. The pump is intended specially for use in producing the vacuum in the globes of incandescent electric lamps, and the exhibition was devoted entirely to this end, but the pump's usefulness does not stop here, since it may be applied wherever a perfect, or as nearly perfect, vacuum as it is possible to get may be required. Hitherto it has been impossible to get the required vacuum in the electric lamps without using the glass mercurial pumps, in which the falling of a column of mercury draws out the air with it. The Berenberg pump, however, accomplishes better results without the use of mercury, and at the same time does the work very much more quickly than the best of the mercurial pumps. The principles of its operation are practically the same as with any piston vacuum pump. Its three exhausting cylinders are made air-tight by means of liquid under heavy pressure, a refined oil being the liquid used.

Exhibition of the power of the pump was first made in exhausting about 20 globes, this being a convenient

number to handle, though it is claimed that only an extension of the apparatus would be required for a pump of this size to do the work on 500 or 1,000 at the same time. The globes were mounted on glass tubes, so that they could be easily sealed and taken from the pump. The greater portion of the air in the globes was taken out almost immediately, probably in two or three strokes of the pump, and the time taken subsequently was in producing the almost perfect vacuum needed in electric lighting. At the end of five minutes a couple of globes were sealed and taken from the pump and the bit of glass tube attached carefully broken off in a vessel of mercury, the result being a rush of the mercury to fill the vacuum in the globe and the consequent indication of the vacuum obtained. It was found that the air bubble left in these globes was only about twice as large as the head of a pin, a very much better result than shown in the lamps of the companies now making them, and in which the vacuum had been obtained by mercurial pumps only after three or four hours' time. Globes taken off in ten minutes showed a bubble hardly larger than a pinhead, and consequently a more perfect vacuum than had been obtained by any other process. The bubbles were also uniform in size in different globes, showing the steadiness of the operation.

The next experiment was to show how quickly the current could be let on to a lamp after exhaustion had begun without burning the carbon, it being explained that in ordinary manufacture at least one hour was allowed to elapse. In less than 10 seconds after starting the pump the half dozen lamps used in the experiment were lighted and burned steadily and brightly, showing that in that short time a vacuum sufficient to prevent the burning of the carbon had been formed. Lamps were also shown, still burning steadily, which had been burning for over 500 hours, this being to show the superior durability of the lamps exhausted by the pump.

The World's Fair in Chicago.

The bill authorizing and indorsing on behalf of the United States the holding of a World's Fair in Chicago in 1892-93 has finally passed both houses of Congress and received the signature of the President. Rivalry between different cities as to where the fair should be held some time ago ceased to be an element in the matter, and Chicago has been the unopposed leader in this respect, but the long delay in making the final authorization by the government had begun to lead people to think that possibly we were not to have any fair at all. Now, however, it is high time for the beginning of actual work, if we are to make the fair the national success it should be, and worthily representative of our position and progress in all the arts, sciences and industries.

The possibility of a high degree of success in such endeavor is, moreover, greatly increased by the fact that Congress has virtually given another year for preparation—that is, although there will be exercises commemorative of the landing of Columbus in October, 1892, the fair proper will not be opened until the spring of 1893. There is also added to the bill a section directing the holding of a naval review in New York harbor in April, 1893, and foreign nations are to be invited to send ships of war to join the United States Navy in rendezvous at Hampton Roads, Va., and proceed thence to take part in the review.

Electric Light Wires in Montevideo.

Early in March one of the electric wires at the corner of Calle 18 de Julio broke and fell on the road. Two horses in a market cart passing by were thrown down by the electric current the moment they touched the wire, which was giving out sparks as it lay on the ground, and the driver was thrown off his seat. A policeman attempted to clear the wire from the horses' feet with his sword, when he was immediately knocked down by the force of the electricity. He managed to get on his feet, but was again knocked down. Some of the lookers-on went and pulled him off the wire, and in doing so one of them was knocked down, but managed to save himself by rolling off the wire. Immediately afterward a tramcar drawn by three horses arrived, and all the animals fell on coming into contact with the wire. By this time the men of the electric light company appeared on the scene. One of them was for a time prevented by the police from touching the wire, but afterward one of them seized the wire with a tongs to try to cut it, and was at once thrown on his back; but the tongs fell from his hands and he was able to get up again. Some more of the company's men arrived shortly after, and the horses were rescued. The men then set about to repair the wire in order to get light in the Calle 18 de Julio and other streets that were in darkness all the time.

An excellent and quick way to mend broken plaster casts and impressions is to paint the broken surfaces over two or three times with very thick shellac varnish, and at each application to burn out the alcohol over a flame. When the shellac is sufficiently soft, press the parts together, and hold in position till cool. It will be as strong as it was before broken.



## THE OIL WELL AT SOUTHBURY, CONN.

BY E. O. HOVEY.

Connecticut has had a peculiar history respecting mineral wealth. Many of the precious and baser metals have been found within her borders in sufficient quantities to lure men to spend thousands of dollars in mining and prospecting, but the deposits have always proved deceptive and unremunerative. Gold, silver, molybdenum, bismuth, nickel, arsenic, copper, iron, and lead, besides other minerals too numerous to mention, occur in many localities in the State; but, with the exception of the iron at Salisbury, Sharon, and Kent, the search for them has been disastrous to every one except the mineralogist, who has been well repaid for his labors.

Coal and oil also have received attention at the hands of eager enthusiasts. Many years ago a boring for coal was made with the diamond drill in the town of Durham, in the south central part of the State. When a depth of about 500 feet had been reached, and before the Triassic rocks had been pierced, the fruitless task was abandoned. Parts of the core from this boring may be found in many private collections in the State.

The occurrence of combustible black shales in the Pomperaug Valley, in the west central part of Connecticut, led some enterprising individuals in 1831 to sink a shaft for coal about a mile west of the village of Southbury, New Haven County. Welsh miners were employed, who sank a shaft six feet square one hundred feet into the rock. At this depth drilling was begun, and carried on for some scores of feet deeper, with the crude apparatus of the day. The story goes that one morning, after a depth of 250 feet had been reached, the miners on descending the shaft encountered a quantity of gas, which ignited from their lamps and exploded. This accident and the increase of water stopped the work, no genuine coal having been found.

About twenty feet from this old shaft a company of Waterbury capitalists began to sink a well in September, 1888, being influenced by the legend of the old well, and by the presence of oil on the waters of a brook near by, to think that oil or gas might be struck by a deep boring. A complete plant from Bradford, Penn., with a twenty horse power engine, was put in, and with a gang of experienced oil well drillers from Bradford work was pushed forward rapidly. Black bituminous shales and red shales smelling of petroleum encouraged the company in their undertaking, and gave even the drillers sufficient faith in the success of the project to lead them to try to lease all the land in the vicinity. The oil fever, however, had struck the Southbury farmers, and no land could be hired. After a series of the mishaps common in the making of deep borings, the depth of 1,525 feet from the surface was attained. Last summer (1889) the job of reaming out the lower half of the well was undertaken; but after it had been partly done the tools were lost, and no work has been done since, though the company has not abandoned the idea of drilling below the 1,525 foot level.

The well is in the south central part of the Woodbury-Southbury outlier of the Connecticut Triassic area. An account of the geology of the region, with map, by Prof. W. M. Davis, of Harvard University, may be found in the "Seventh Annual Report of the United States Geological Survey," issued in 1889. The well intersects red and black shales, red sandstones and conglomerates, and two trap sheets, and at about 1,235 feet passes from the fragmental Triassic rocks into the highly crystalline gneisses and mica schists so widely distributed throughout New England. It is of interest to note that this is the first recorded instance of a boring which has pierced the Triassic rocks of this State.

At 1,250 feet free-milling gold and silver-bearing rock was struck, which assayed \$10 worth of gold and \$3 worth of silver to the ton, and the rock for ten feet above and twenty feet below this depth shows this amount or more of silver. If this rock occurs in considerable quantities, it would well repay the outlay necessary to mine it, and some of the oil well companies propose sinking a well with the diamond drill to obtain more definite knowledge of the strata and the occurrence of gold-bearing rock.

Speaking from geological premises, there is no chance whatever of obtaining either oil or gas from any boring here or elsewhere in Connecticut. The Triassic rocks are far above the strata which yield oil or gas in other States, while the crystalline rocks, which form the remainder of the State and are mostly of uncertain age, have been so highly metamorphosed that all volatile constituents like oil and gas—if ever there were any—have entirely disappeared from them.

A LOAN association in this city recently invited a number of persons to hear a speech by the celebrated English statesman Mr. Gladstone. It was a phonographic oration. That is to say, a phono-cylinder was produced, stated to have been just received from London, and when the cylinder was put through the phonograph machine a voice was heard, said to be Mr. Gladstone's. The message was short and rather dry. It related to self-help and thrift, both of which are very desirable qualities, according to Mr. Gladstone.

## School of Industrial Art and Technical Design for Women.

At a reception held recently at the School of Industrial Art and Technical Design for Women, 134 Fifth Avenue, New York City, Miss Katherine Smith, a pupil and the "historian" of the school, read a paper which was in substance as follows:

When in the fall of 1881 a class of five was instructed by Mrs. Florence Elizabeth Cory in the principles of design and taught to apply them practically to industrial arts, then was first established the organization known as the "School of Industrial Art and Technical Design for Women." From that nucleus sprang the prosperous school which at present has upon its roll of membership 490 names, correspondent pupils inclusive, all of whom are striving to attain a degree of proficiency in their several departments of practical designing and industrial handicraft that will enable them to become self-supporting. Among these students are representatives of every State and Territory in the United States, several Canadian cities, and the Sandwich Islands. During the first two or three years lectures were given to the students by prominent artists and designers, but these were discontinued because the classes soon assumed such proportions that there was not room enough to accommodate all who wished to hear them.

Numerous invitations have been extended by manufacturers in New York and vicinity to visit their factories, and prizes amounting to several hundred dollars have been offered for various designs, and a variety of valuable art specimens presented.

Many designs have been made and sold to manufacturers since the establishment of the school. The work done has included carpets of all grades, oil cloths, linoleums, wall papers, stained glass, carved and inlaid wood panels, printed silks and silkalines, ribbons, upholstery fabrics, portieres, table linen of all kinds, calicoes, prints, awnings, lace, fan mounts, book covers, china, Christmas, Easter, and menu cards. Not only have orders have been filled for American manufacturers, but there have been sent to Leeds and York, England, patterns for ingrain, to Carlsbad, Austria, designs for china, to Dundee, Scotland, patterns for table linen and towel borders, to Japan, designs for printed and embroidered silks.

## What the Best Judges Declare an Invention to Be.

The late Judge Hall, of the United States Circuit Court, says:

"An invention, in the sense of the patent law, means the finding out, the contriving, the creating, of something which did not exist and was not known before, and which can be made useful and advantageous in the pursuits of life, or which can add to the enjoyment of mankind.

"In other words, the thing patented must be new; and it must be useful to an appreciable extent, though the measure of that usefulness is not material. Any degree of utility appreciable by a jury is sufficient, upon the question of utility, to sustain a patent." (Conover vs. Roach, vol. iv. Fisher's Patent Cases, p. 16.)

And Judge Sawyer, late of the Supreme Court of the United States, defines invention in the following language:

"Invention is the work of the brain, and not of the hand. If the conception is practically complete, the artisan who gives it reflex and embodiment in a machine is no more the inventor than the tools with which he works. Both are instruments in the hands of him who sets them in motion and prescribes the work to be done. Mere mechanical skill can never rise to the sphere of invention. The latter involves higher thought, and brings into activity a higher faculty. Their domains are distinct. The line which separates them is sometimes difficult to trace; nevertheless, in the eye of the law, it always subsists. The mechanic may greatly aid the inventor, but cannot usurp his place." (Blandy vs. Griffith, vol. iii. Fisher's Patent Cases, p. 616.)

But while, as Judge Sawyer asserts, the boundary line between the domain of invention and mere mechanical skill is strictly drawn, yet some of the most valuable inventions have been so simple as to lead one to think that they were obvious, and did not rise to the dignity of invention.

Concerning the simplicity of invention, the late Judge Story, of the Supreme Court of the United States, remarks:

"The simplicity of an invention, so far as being an objection to it, may constitute its great excellence and value.

"Indeed, to produce a great result by very simple means, before unknown or unthought of, is not unfrequently the peculiar characteristic of the very highest class of minds." (Ryan vs. Goodwin, vol. i. Robb's Patent Cases, p. 729.)

It not infrequently happens that a sudden lucky thought gives a man a small (sometimes a large) fortune—the outgrowth of an important invention.

More than a quarter of a century ago, the late Judge Shipman of the United States Circuit Court of New York embodied the idea in one of his decisions:

"A subject matter to be patentable must require invention; but it is not necessarily the result of long and painful study, or embodied alone in complex mechanism. A single flash of thought may reveal to the mind of the inventor the new idea, and a frail and simple contrivance may embody it. Some inventions are the result of long and weary years of study and labor, pursued in the face of abortive experiments, baffled attempts, and finally reached after the severest struggles; while others are the fruit of a single happy thought." (Magic Ruffle Company vs. Douglas, vol. ii. Fisher's Patent Cases, p. 338.)

Other opinions, similar in purport, might be added; but these are sufficient to define what constitutes a patentable invention, which is important information for every inventor to know.

## A Smokeless Powder.

A new explosive in the line of smokeless powder has recently been invented and patented by Sir Frederick A. Abel, of London, and Professor James Dewar, of Cambridge, England. The authors say:

The gelatinous explosives produced by combinations of nitro-cellulose and nitro-glycerine, with or without other ingredients, exert great disruptive force when they explode, and are, therefore, not suited for ammunition purposes.

The present invention relates to an improvement in the manufacture of such explosives whereby we moderate the force and rapidity of their explosion, giving it a propulsive instead of a disruptive character, so that they are adapted for ammunition purposes, the permanency of the compound without change being at the same time secured. For this purpose we combine tannin with the nitro-cellulose or nitro-glycerine, or with both in either of two ways. We either dissolve the nitro-cellulose—such as gun cotton or pyroline—by any of the known solvents—such as acetone or acetic ether—and we add the tannin ingredient to the solution; or we first dissolve the tannin ingredient in the acetone or its analogue and use this solution as the medium of incorporation with the nitro-glycerine. We thus produce a compound which, when the solvent is eliminated by extraction with water or by evaporation, or both, is a tough, hard substance that can be granulated or otherwise treated for use as an explosive.

Instead of employing nitro-cellulose alone in forming the compound, as above described, we employ with it various proportions of nitro-glycerine, and we thus obtain a compound of soluble nitro-cellulose or of gun cotton (insoluble nitro-cellulose) with nitro-glycerine and tannin in a gelatinous condition, which may be rolled into sheets, drawn into wire, or otherwise treated for use as an explosive.

With the compounds produced as above described may be incorporated various proportions of oxidizing agents—such as nitrates of potassium, sodium, ammonium, and barium—and oxidizable substances—such as lamp black or graphite—and hydrocarbons—such as paraffine, vaseline, and naphthalene, cellulose, fatty oils, and fats or nitro-derivatives of hydrocarbons.

The proportion of tannin added for the purposes of our invention may be varied. In treating gun cotton alone we have found the proportion of ninety parts of gun cotton and ten parts of tannin to give good results.

In the case of a compound of gun cotton and nitro-glycerine we have employed the following proportions with advantage:

	Per cent.	Per cent.	Per cent.
Nitro-glycerine.....	55	35	40
Gun cotton ..	35	55	40
Tannin.....	10	10	20

Under the term "tannin" is to be understood any of the substances that are sold commercially under the name of "tannic acid." We prefer, however, to use gallo-tannic acid for the purpose of our invention.


## Waste of Gas.

Chemist Martin, of the New York Board of Health, made an important statement before the Senate Investigating committee recently in relation to the comparative dangers of electric lighting and gas. He says that 10 per cent. of the gas manufactured in New York escapes from the mains into the earth and permeates the cellars and basements of the buildings and residences throughout the city. In addition to the injurious effect this has on the health of the city, it is also manifestly evident that there is great danger to life and property through explosions which must follow the introduction of gas into sewers and subways. The *Western Electrician* thinks one thousand million feet of gas contain more danger than the electric conductors in New York City, yet this is the amount, according to the same authority, but which is hard to believe, that leaked from the mains of the gas companies of this city last year.

DURATION OF LIFE IN NORWAY.—According to a recent work on longevity, published in Norway, the average duration of life in that country is 48.33 years for men, and 51.3 for women.

**AN IMPROVED AUTOMATIC DUMB WAITER.**

The accompanying illustration represents an improvement in hatchways, whereby an automatic opening of the hatches is effected by the cage as it ascends or descends, the hatches also automatically closing after the cage has passed. The invention has been patented by Mr. John Stoneham, of No. 58 Clinton Place, New York City, and is also applicable in the building and operation of freight and passenger elevators, as well as for dumb waiters, in which connection it is shown in the illustration. Between each pair of platforms in the hatchway is a grooved guideway, T-shaped in cross section, in which slides a stop, connected by a rope passing over pulleys, just under the floor above and at the side of the guideway, to the forward end of the hatch covering below. The lower portion of this guideway is not grooved, and has an offset beneath which the hatch cover is received when raised, so as to clear the cage. A flange of the stop slides in the cross groove of the guideway in a line slightly in-



STONEHAM'S AUTOMATIC DUMB WAITER.

clined from the vertical, the inclination being such that the stop is entirely concealed in the guideway when in its lowermost position, while projecting well out when in its uppermost position. The cage rising from below therefore pushes up the hatch cover and readily passes the stop, which it has first caused to drop to the lowermost position by the raising of the hatch cover, and then holds in until it has entirely passed it. The stop is then caused to press against the bottom of the cage by means of its rope and pulley connection with the hatch cover below, until the latter is entirely closed, when the stop will be in its uppermost position, and will project out of its grooved guideway to its entire extent. Upon the descent of the cage a beveled finger on its bottom bears upon the stop to push it down and gradually open the hatch below, as each succeeding opening is passed, the covers gradually closing over the cage as it goes down. It is obvious that the construction here shown presents great advantages in its perfectly automatic manner of closing as well as opening the hatches, whereby the great

danger of fire from open shafts communicating with the different floors of a building is avoided. In the use of such construction, also, for freight and passenger elevators, with the application of power therefor in any of the ordinary ways, it is evident that many of the dangers incident to ordinary systems would be avoided, as the hatches would all be closed except the one which the car was at the time passing, and it would not be possible for a car to fall for any considerable distance from any carelessness of the attendant or the breakage of any of the parts, as it would be impossible for the automatic action by which the hatch covers are opened to take place with sufficient rapidity to allow a car to fall from the top to the bottom of a shaft.

**J. G. Halske.**

The death is recorded, at Berlin, of Herr Johann Georg Halske, the co-founder and, for many years, partner of the well known firm of Siemens & Halske. He was born at Hamburg on July 30, 1814, and went to Berlin, where he set up an engineer's shop in 1844. Soon after he made the acquaintance of Werner Siemens, and it was in Halske's workshop that Werner Siemens, assisted by the mechanical skill of the former, was able to work out his first inventions in telegraphy, so as to bring them before the public. In 1847 the two men entered into partnership and laid the foundation of the telegraph construction works which at the present day give employment to thousands of workmen, both at Berlin and Charlottenburg, and at several branch establishments. Halske left the firm in 1867, and since then has been an active member of the municipality of Berlin.

**A Balloon with Compartments.**

Mr. Andre Mahoudeau describes, in *Les Inventions Nouvelles*, a new kind of balloon devised by him, and divided into several compartments, according to the principle applied in navigation. One of the advantages of this system is that a rent in the balloon does not imperil the life of the aeronauts.

Each compartment is provided with a pipe that descends through a central funnel. In this way, it is possible to inflate the compartments independently of one another, and with gases of different natures.

This arrangement is necessarily accompanied with a certain increase in weight, but this is but 77 pounds for a balloon of 6,700 cubic feet capacity.


**AN IMPROVED WATER TOWER AND EXTENSION LADDER.**

In the machine represented in the accompanying illustration, telescoping pipes form the water tower, with split glands and a screw on the end for locking each pipe in place on to the next following pipe. The invention has been patented by Mr. Edwin Crippen, of No. 18 North Broad Street, New Orleans, La. The exterior pipe is pivoted at one end on a turntable, and moving pistons are pivotally connected with it above its fulcrum, with fixed inclined cylinders, in which the pistons are made to travel by means of compressed air, there being an intermediate mechanism for pivotally connecting the pistons with the exterior pipe. The machine has reservoirs charged with compressed air, and of a capacity double the amount necessary to extend the tower to its extreme height, while a small air pump is mounted on the apparatus to charge the reservoirs and keep the pressure substantially uniform at all times. The exterior pipe has solid trunnions, and a pipe between them forces air into the telescoping pipes, links being pivotally connected with the exterior pipe, and piston rods connected with the links to operate pistons in fixed inclined cylinders, with means for locking the exterior pipe to the cylinders.

The apparatus has an extension ladder comprising a series of sections, one of which is secured to the central telescoping pipe, and the sections have hooks and staples whereby one section may be readily made secure to the next following section, there being guiding brackets for the ladder sections and screws for locking them in place. The apparatus when raised in position is to be supplied with water under pressure, as usual, from fire engines or other sources, and has a flexible nozzle or play pipe, the valve communicating with which can be opened from the ground by pulling a rope. The water is directed on to the fire by an operator standing on the platform at the upper end of the largest or lower section of telescoping pipe. The apparatus may also be used as an extension ladder without a fire engine, and the ladder can be turned in any direction by the operator taking hold of the legs to turn the turntable. The tower and the extension ladder may then be inclined so that the upper part of the ladder or tower may lean against the building, and form a means of communication therefrom to the ground.

**AN IMPROVED BRACE FOR PIANO STRING FRAMES.**


An invention designed to provide for the support of piano strings in such a manner that they will retain their pitch, but will be held with a certain amount of elasticity, adapted to insure a rich, full, mellow tone, is illustrated herewith, and has been patented by Mr. John Jaworsky, of No. 156 Bergen Street, Brooklyn, N. Y. Fig. 1 is a rear view, and Fig. 2 a cross section of a frame in which this improvement is embodied.



JAWORSKY'S BRACE FOR PIANO STRING FRAMES.

That the wrest-plank may be held against undue yielding by strain from the tension of the strings, iron braces are employed, with upper forwardly extending lips upon which the wrest-plank fits, and with lower forwardly extending lips which rest upon and extend in advance of the sill. The braces are centrally divided to form vertical lengths, and have upwardly extending slotted tongues to provide for the passage of the retaining bolts. The sounding board is secured to the end braces, and extends in advance of the iron braces and intermediate wooden braces arranged in the spaces between the iron braces. The tuning pegs are secured to the wrest-plank in the ordinary way. This frame is designed to render the use of the rigid cast iron plate unnecessary, leaving the sounding board free to respond to the vibrations of the strings, which, being supported at their upper ends by wood, assures a certain amount of pliability and elasticity, while the wooden frame is sufficiently braced for the retention of the pitch to which the piano has been tuned.

**ADULTERATION OF AN ADULTERANT.**—The United States consul at Stettin in a recent report calls attention to the adulteration of the chicory exported from




CRIPPEN'S WATER TOWER AND EXTENSION LADDER.

there. From inquiries which he made he learned that the larger part of the chicory is made from beet roots, dried and burnt or roasted, and prepared in the same manner as pure chicory. The mixture usually sold as chicory is composed of one-third of the pure article and two-thirds of roasted beet roots. It is invoiced at about 1½¢ per pound, a price at which it is quite impossible to get genuine chicory.



**AN IMPROVED TIME REGISTER.**

The illustration represents a register designed as a convenience in factories, mills, etc., to facilitate keeping the correct daily time account of the work of each individual. It has been patented by Mr. Leverett W.



**TIFFANY'S TIME REGISTER.**

Tiffany, of Winsted, Conn. Figs. 2 and 3 are views in perspective, and Fig. 1 is a sectional plan view. The time sheet is placed on rollers within the casing, one roller being, as shown in Fig. 1, on each side of a table over which the sheet is drawn so that it may be readily marked upon with a pencil or pen through an opening or slot in the cover. The slot is preferably formed by spaced glass plates fitted in the cover. Beneath the plate

applied to turn the time sheet back except by one having a key to the cover. The time sheet is preferably ruled for each day in the week, and adapted, as shown, to bring the columns in line with the opening in the slot.

**NEW GERMAN ARMOR-CLAD CRUISERS.**

As regards naval affairs, the Germans seem to be collecting their thoughts. They are devoting much study to foreign fleets, but are constructing nothing very new. It would seem that no programme has as yet been definitely resolved upon. The use that is to be made of the extraordinary appropriation that has just been voted is kept a secret. We propose to make known at present two of the modern cruisers of Germany—the Irene and the Princess Wilhelm, which belong to a new type called on the other side of the Rhine the protected cruiser.

The Irene, which we shall alone describe, displaces 4,400 tons. She is 308 feet in length and 45 feet in width. Her engine is of 2,000 horse power. She made 18 knots an hour on her trial trip.

This vessel is protected solely along her coal bunkers. It is provided with an armor plate deck strongly curved, so as to descend to a considerable depth below the load water line. The engines, two in number, are placed in distant compartments totally independent of each other. Each of them actuates a screw under cover of the lines of the stern. The supply of coal and ammunition is very large. Cruisers of this type have to navigate by steam only, and their masts, which are military ones solely, are deprived of yards.


The armament consists of a barbette battery of 14 six inch guns, one on each side, away forward, firing through a port hole. Four sponsons, permitting of firing fore and aft, contain, each of them, one gun, and comprise between them the eight other pieces, which are placed simply upon the deck and have but quite a

there being, lower down on the upright, laterally extending arms or brackets having bearings for a horizontal guide roller. A small horizontal platform is held suspended by means of coiled springs from the upper end of the upright, and has a perforation for the passage of the hoisting rope. The windlass shaft has a balance wheel at each end, and at one end is pivoted a bell crank lever with a shoe on its lower arm adapted to bear against the periphery of one of the balance wheels, thus constituting a brake which may be easily manipulated.

For further particulars with reference to this invention address Thomas H. Bridges, the patentee, Valley Mills, Texas.

**AN IMPROVED SHAFT LIGHTER.**

The construction shown in the accompanying illustration is designed to provide for directing the rays of




**STEVENSON'S SHAFT LIGHTER.**


the sun downward upon one spot at all hours of the day, Fig. 1 being a perspective view of the device and Fig. 2 showing its application to a light shaft or well. The invention has been patented by Mr. Hugh Stevenson, of 155th Street and St. Nicholas Avenue, New York City. A frame of horseshoe form is mounted at the top of the light shaft, the convex end of the frame toward the north, and its free ends adjusted to an angle of about forty-five degrees. On its inner side the frame has a series of reflecting surfaces. The convex end of the frame is supported by a bracket, and its extending ends rest loosely upon brackets at the sides. Each end of the frame is connected by two rods, one over the other, with the side walls of the light shaft, the rods carrying nuts, whereby the ends of the frame may be adjusted at a proper angle to reflect the light down the shaft. In the summer the convex end of the frame should be practically vertical, but in winter a slight angle of inclination is desired, and to effect this two rods are made to extend from this end of the frame to a fixed support, the rods being so proportioned as to length that the winter temperature will contract them sufficiently to give the required incline. With this construction, as the sun travels round, it bears successively, from its rising till its setting, upon the different reflecting surfaces of the horseshoe frame, from one end to the other.

**AN IMPROVED ANIMAL BED.**

A bed designed more particularly for horses, and so constructed as to be durable, dry, and comfortable, while adapted for use with or without the ordinary straw bedding, is shown in the accompanying illustration, and has been patented by Mr. Hugh Stevenson, of 155th Street and St. Nicholas Avenue, New York City. The bed is formed of elastic tubes, preferably made of rubber, and held in place by transverse strips and binding strips to constitute a number of series of practically air-tight chambers. The compartments may be formed after the tubes have been vulcanized, by drawing the binding strips down tight. There are sufficient spaces between the aligned cushions thus provided to insure thorough ventilation and cleanliness.



**STEVENSON'S ANIMAL BED.**



**NEW GERMAN WAR SHIP, THE IRENE.**


at the right is held a narrow slate on which the names of the employes are written, as shown in Fig. 3. The rollers are turned to shift the time sheet by a key inserted in holes at one end of the casing, and to prevent their turning back they are journaled in a spring plate which lifts them against the top of the main frame and acts as a brake. Attached to the cover is a plate adapted to enter a slot in the main frame when the cover is closed, and wholly prevent a key from being

limited field of fire. Upon the shields and in the tops are installed eight revolving guns. Three torpedo tubes are placed at the extremity of the ship. The Irene carries a crew of 320 men.

Let us add that the present German fleet comprises five ironclads remodeled prior to 1870. In case of war, these vessels would form an open sea squadron. The defense of the coasts would be assumed by four cruiser corvettes, without masts, making scarcely 12 knots per hour. The German navy includes in addition the ironclad Aldenburg, a remarkable vessel, 21 gun boats, and an old monitor, the Arminius. Its cruisers are well armed, and its torpedo boats are numerous. There are also special gun boats, which carry 8 guns, and are designed for Africa.—*La Nature*.

**AN IMPROVED WINDLASS.**

The illustration herewith represents a windlass specially designed for hoisting well buckets and similar uses, and to be rapidly operated with the least possible expenditure of power. The several parts of the frame are bolted together, and its foot pieces have perforations for bolts for securing the windlass in position. The windlass shaft is mounted in bearings in the ends of the frame, and at one end has a small pinion meshing with a large gear wheel, a spur wheel meshing with this gear wheel, the spur wheel having an operating crank. In the front brace or crossbar of the frame is mounted an upright, the upper end of which has a grooved pulley, over which passes the hoisting rope,



**BRIDGES' WINDLASS.**



**Practical Hints on Cobalt Plating.**

BY ALEXANDER WATT.

Since cobalt as a coating for other metals, as brass, copper, and steel, for instance, presents some advantages which would render cobalting a useful substitute for nickel plating, I have lately made a series of experimental trials with a view to point out as far as possible the most favorable conditions under which successful and uniform results may be obtained in the deposition of this metal for practical purposes. Cobalt, being a whiter metal than nickel, would be a useful coating for ornamental brasswork, as also for small fancy articles in which a cheap white metallic film is desirable. Being softer than nickel, articles coated with cobalt may readily be brightened by burnishing, a process that could not advantageously be applied to nickel-plated surfaces. Like nickel, cobalt is a non-oxidizable metal, and therefore retains its color in ordinary atmospheres. Although cobalt is a dearer metal than nickel, I am disposed to think that its employment as a substitute for the latter metal would not in the long run greatly exceed, if at all, that of nickel-plating, and for the following reasons: Only one-third of the quantity of "salts" are required to make up a bath; about one-third of the anode surface is required; the deposited metal, being softer than nickel, naturally requires less labor in finishing; and, finally, less current is required than for nickel. Taking, therefore, these points into consideration, they will probably be found to balance those in favor of the cheaper metal. As to the difference in value of the respective metals when actually deposited upon the work done, this might probably be counterbalanced by extra charges for the cobalting articles, which might reasonably be demanded so long as the cobalting remained a novelty.

In making up a bath, the salts employed were the double sulphates of cobalt and ammonia, this compound being practically the most suitable for commercial purposes; and in order to ascertain the proper density at which the bath should be prepared, solutions of various densities were tried, and the one which appeared to yield the best results was selected. The next point to determine was the density of current which would give a perfectly adherent deposit of good color, and free from "burning" at the corners of a flat plate or projecting surfaces of an article. After making many modifications in the strength of the solution, it was found that a bath of the specific gravity of 1015 (water being 1,000) at 60° F. gave the best results, and this was obtained by dissolving 4½ oz. of the double sulphates of cobalt and ammonia in one gallon of water. This solution worked most favorably with a current of about 0.800 ampere, the E.M.F. being about two volts. The electrodes used in the first trials were a well-cleaned brass plate 3 in. by 2 in. for the cathode, while the anode consisted of a plate of rolled cobalt, supplied by Messrs. Henry Wiggin & Co., of Birmingham, from whom also the cobalt salts were obtained. The next point to determine was the amount of anode surface which was necessary to admit of a prompt deposit, and yet not too quick for an adherent film. With the current named, and about equal electrode surface, it was found necessary, after a few minutes' immersion of the brass cathode, to remove a considerable portion of the anode from the bath, in consequence of the plate becoming blackened or "burnt," as it is termed, at the corners; when the surface of the anode was reduced to about one-third that of the brass plate, deposition took place with perfect uniformity, and there was no longer the least tendency to the discoloration referred to. It thus became evident that an important consideration in the electro-deposition of cobalt is the amount of anode surface which is most suitable in a cobalt bath of a given density. In nickel-plating, as is well known, this is not a matter of so much importance, and it is commonly the practice to employ a very large surface of anodes in the baths, almost regardless of the actual surface presented by the articles suspended in the solution. My object in directing special attention to this difference between the operations of cobalting and nickel plating is that I believe that one of the reasons why the electro-deposition of cobalt has not been successful in some hands is that too little attention has been paid to the detail I have pointed out.

To prepare a solution bath for cobalt plating, 4½ oz. of the crystals of double sulphate of nickel and ammonium for each gallon of the bath should be dissolved in hot water, and the solution then made up to the required quantity by the necessary addition of cold water. The solution should then have a specific gravity of about 1015 at the temperature of 60° F. For the successful deposition of cobalt upon articles formed of brass, copper, steel, or iron, the anodes may be of rolled cobalt, in narrow strips, say about 2 in. wide and 12 in. to 18 in. long, according to the size of the depositing tank. The anodes should be placed about 6 in. apart along the sides of the tank, and in the case of large tanks, say vessels holding 200 or 300 gallons or more, a corresponding series of anodes should be suspended from a conducting rod placed lengthwise, and resting on the ends of the tank, as in nickel plating, etc. All work to be coated with cobalt should be

polished and prepared for the solution precisely in the same way as for nickel plating, and before they are immersed in the bath the current must be so regulated that the work may become coated with a film of metal, or "struck," as it is termed, within a few seconds after being placed in the bath. There need be no fear of the work stripping—provided it has been properly potashed and scoured—if the articles become coated immediately after immersion, but in this case the current must be at once reduced, otherwise the work is sure to "burn," or become discolored, at certain parts in a few minutes after. It is far preferable, indeed necessary, after the first film has been obtained, to immediately diminish the current, this being again augmented when other articles are put into the bath. By watching the rate at which each article becomes coated, and regulating the current accordingly, the probability of burning the work will be readily overcome. My reason for directing special attention to this is that cobalt deposits so much more readily than nickel that any person unacquainted with the deposition of cobalt and treating it as he would nickel might naturally fall into error, readily avoided, which would cause failure and disappointment. It should always be the rule, therefore, in cobalt plating to diminish the current so soon as the article is fairly coated all over, but more especially is this the case when the work becomes coated instantly after immersion. Since copper does not appear to receive a deposit of cobalt quite so readily as brass with the same amount of current, it will be found advisable, when copper articles are to be cobalting, to start with a somewhat stronger current than would be required for the yellow alloy; but when the piece of work has fairly struck all over with the stronger current, this must afterward be reduced somewhat during the remainder of the time the article is in the bath. In cases where a dead cobalt surface is required, the articles, having been dipped in the usual way, may be scoured with powdered pumice, or, still better, with powdered bathbrick, and after rinsing placed in the bath, using a rather strong current at first, and reducing it after the work is coated all over. If such articles have projecting points, these must not be allowed to approach too close to the anodes, otherwise such parts will be apt to become dark; should such be the case at any time, however, the piece of work must be removed and again scoured at the discolored spot and then rinsed and returned to the bath, a weaker current being used. All dead work, after removal from the bath, should be plunged into clean boiling water and allowed to dry spontaneously, care being taken not to handle the work at such parts as will be required to present a clean white surface. When a brighter surface is required, the work may be scratch-brushed at the lathe with brushes made from fine steel wire, moistened with beer in the usual way, after which the pieces may be dipped in a solution of cyanide of potassium, and finally rinsed in boiling water and then put into clean box sawdust. Buttons and other small fancy brass articles may be treated in this way.

In depositing cobalt upon steel or iron surfaces a much weaker current is required than for either brass or copper. The current from a single Daniell cell is amply sufficient for coating small steel articles, and, since cobalt adheres very firmly to this metal, it will be found useful for imparting a white coating to many articles formed of steel or iron. It is also important to note that steel articles coated with cobalt may be brightened by ordinary burnishing, for, as before observed, cobalt is softer than nickel and yields very readily to the pressure of the burnisher. When depositing cobalt upon cast iron, a rather strong current must be used to secure an immediate coating after the work has been placed in the bath, after which, as before, the strength must be diminished and sustained at a uniform density until a sufficiently stout coating is obtained. Here, again, it is necessary to point out that projecting surfaces must be kept as far away from the anode as possible, so that those portions may not become discolored or "burnt" and necessitate rescouring.

There is another feature in cobalt depositing which presents an advantage over nickeling which it is well to mention, namely, that when it is found necessary from any cause to rescour a piece of work and return it to the bath until finished, the operator need not fear, I believe, that the work will be liable to strip after the second coat has been given, for I have generally found that brass and even steel surfaces may be frequently rescoured and cobalting again and again without the metal stripping in the least degree. In the case of nickel we all know that the deposition of film upon film of this metal is almost invariably succeeded by the second coating separating from its predecessor. It may be further remarked that the rescouring of the work, to produce an improved surface upon a defective film, can scarcely be applied to a nickel-plated article, owing to the extreme hardness of the metal. With respect to cobalt, however, the case is different, for with good brisk brushing with pumice, silver sand, or bathbrick reduced to a powder, I have found no difficulty in producing the surface necessary

for a satisfactory deposit of the metal when from various causes it was found necessary to repeatedly rescour the plates used in the experimental trials referred to. In no instance, however, did the subsequent layers of cobalt strip or peel off the metal already deposited.

Some attempts were made to deposit cobalt upon zinc from the double sulphate solution, but in each instance it was found that the film was non-adherent, except in portions of surface where partial adhesion of the metals occurred. Although there are some other solutions of cobalt than the above which would be more suitable for cobalting zinc, it is somewhat doubtful whether a really good deposit of cobalt on this metal could be obtained with any degree of certainty.

In working the solution prepared from the double sulphates of cobalt and ammonium, it appears to be necessary to maintain the liquid at as uniform a density as possible, and for several reasons. For instance, if the bath be allowed to acquire a higher density than about 1,015, by the spontaneous evaporation of a portion of its water, the color of the deposit will probably become affected, and a darker tone imparted to the articles instead of a tolerably good white characteristic of electrolytic cobalt when deposited under more favorable conditions. To obviate such a defect in the metallic strength of the bath, the hydrometer should be floated in the liquid at least once a week, especially in warm weather; and whenever the solution indicates a higher density than it originally had, an addition of water must be made until the specific gravity has been reduced to the proper figure. These additions of water, however, should be made in the evening, or when the bath is not being used, and the solution must be well stirred, and then allowed to rest for at least 12 hours. It is also necessary to avoid adding an excess of water, since a solution much weaker than that indicated will be apt to cause the deposit to be patchy, and certain parts of the article may for a time refuse to receive the deposit. These observations are based upon results actually obtained under the conditions referred to, but the defects may readily be avoided by adopting the precautions suggested.

Respecting what is understood as the color of the deposit, this is greatly influenced by the strength and tension of the current. For instance, it is perfectly easy to obtain film of cobalt upon brass surfaces with an E. M. F. of one volt and a large surface of anode, but this deposit will not be so white as when the current has an E. M. F. of two volts, with small anode surface—that is, about two-thirds less than that of the cathode, or article to be coated.

With respect to the purposes to which cobalting is most applicable, these may be taken as being, on the whole, similar to those for which nickel plating is adopted, but, like the latter metal, it should never be applied to culinary or drinking vessels, since it is, like nickel, readily acted upon and stained by vegetable acids, vinegar, for example, beer, and also by vegetable infusions, such as tea, the water in which cabbages have been boiled, and other liquors of a similar nature. Cobalt also resembles nickel in becoming dull when long exposed to damp atmospheres, and should not, therefore, be employed for articles which are required for out-of-door ornamentation, unless the surfaces can be persistently rubbed over with a dry leather every day. On the other hand, cobalt plating may be adopted for any class of art metal work which is destined to remain in ordinary dry apartments, as fenders, fireirons, etc., or for ornamental work to be worn on the person. Mullers, sausage warmers, dental instruments, and cast brasswork, such as lavatory taps and so forth, may be advantageously coated with cobalt, the articles being prepared and finished as before observed precisely in the same way as in nickel plating.—*Electrical Engineer, London.*

**New Zealand Sulphuric Acid Works.**

The long-closed sulphur works at Tauranga, 100 miles south of Auckland, are about to be opened, and utilized in the manufacture of sulphuric acid, by Messrs. Sharland & Co., of Auckland. On a small islet, called White Islet, some miles off the coast, there is an inexhaustible supply of crude sulphur in a high degree of purity, but, owing to the lessee and part owner of the island refusing to allow it to be worked, this source is not available; but at Matata, some 50 miles south of Tauranga, there is another enormous deposit of sulphur. Other localities, too, not far removed are rich in this element, and the proprietors of the works will have no difficulty in obtaining supplies.

**PRESERVE FOR BINDING.**

The publishers of the SCIENTIFIC AMERICAN would advise all subscribers to preserve their numbers for binding. One year's issue (52 numbers) contains over 800 pages of illustrations and reading matter. The practical receipts and information contained in the Notes and Queries column alone make the numbers worth preserving. Persons who have subscribed since the commencement of this year can have the back numbers sent them on signifying such wish. Their subscription will then expire with the year.



### THE WESTINGHOUSE INTERLOCKING SWITCH AND SIGNAL SYSTEM.

(Continued from first page.)

only drawn back and pushed forward a trifle corresponding to the versed sine of the same arc, 1-2. From 2 to 3 the first relations are re-established; the lock bolt is thrust forward into the hole in the lock bar and the switch is hardly moved at all. A detector bar is worked simultaneously with the lock bolt by means of the rod, F, of the perspective drawing.

Referring again to the cut of the switch board,\* a series of studs or latches are seen projecting through holes below the switch handles. These, if moved upward, catch the lower projecting ends of the switch handles. They are raised and lowered by the agency of the signal handles. As each of these is moved it throws a notched bar that runs parallel to the face of the case to the right or left. The bar, according to the arrangement of the notches, throws upward or permits to drop any one or more of the latches. When raised a latch locks the lever above it, when depressed it frees it. Thus a mechanical interlocking of switch and signal handles is provided that by different disposition of notches may make the movements of one or more switch handles depend upon the movements of any given signal handle.

On the rear end of each signal spindle on the switch board is a quadrant which swings to right or left as the spindle is rotated. This has teeth in which a latch engages. This latch is operated by an electro-magnet in the rear included in the independent signal circuit just described. When the signal is at "safety," this circuit is open, and the magnet not attracting its armature, the latch, by gravity, locks the quadrant as to allow only a small degree of movement to the signal handle with its spindle. This movement is enough to close the main circuit and thus release the semaphore, which rises to "danger," but not enough to lower the interlocking latch or latches projecting from the front of the case, until the semaphore has risen the full distance to "danger." As it reaches this position




Fig. 3.—SIGNAL—MOVING MECHANISM.

the auxiliary or locking circuit is closed, the magnet attracts its armature, drawing the quadrant latch out of engagement with the quadrant, and the handle can now be swung clear over, unlocking the switch handles dependent upon it.

On the rear end of the switch spindle in the switch board are similar quadrants, whose locking latches are actuated by an electro-magnet connected with the circuit breaker on the switch-throwing mechanism. At the end of the locking bolt, H, of this mechanism, Fig. 1, is a circuit opener. When the bolt is in place and the switch locked as shown, the circuit is open. This opener is in circuit with the electro-magnet back of and actuating the quadrant-locking latch appertaining to its own spindle on the switch board. This is so constructed that a limited movement only is allowed when the circuit is open. This movement is enough to turn the three-way cock. The switch begins to move. As the locking bolt, H, Fig. 1, comes back, the circuit closes. The magnet attracting its armature unlocks the quadrant and instantly relocks it. This is done so quickly that the handle cannot be moved during the change. The switch continues its movement. As it is thrown and locked, the circuit opens, the quadrant is free, and the handle can be swung clear over. Its first movement was only sufficient to open the cocks, but not enough to close the signal-actuating circuit by the strips of metal on its spindle. This is done by the second motion. Hence as the signal cannot be moved until this circuit is closed, and as a semaphore cannot be set at safety without this closing of circuit, the protecting semaphore cannot be set at "safety" until all the switches in its system have been completely thrown and locked by the regular locking bolt.

Above the case containing the switch and signal handle mechanism and connections, and facing the operator, is a miniature model of the tracks and switches controlled by the switch board. The model has movable

\* We are indebted to Messrs. Charles Scribner's Sons for the use of this cut, which was published in "The American Railway."

switches, which repeat the movements of the actual switches, so that at a glance the operator can see what position every switch in the system occupies. An annunciator drop is also placed in view of the operator. This is worked electrically by any train approaching the system, which train causes a bell to ring and also drops the shutter when it is within a mile of the track yard.

### New Hoisting Plant of the Calumet and Hecla Mining Company.

The new hoisting plant recently built by the Calumet and Hecla Mining Company, at Calumet, Mich., is one of the most elaborate ever erected. It consists, says the *Engineering and Mining Journal*, of three triple expansion, vertical inverted beam engines, designed to hoist 10 tons at a speed of 2,000 feet per minute. The cylinders are 18 inches, 27 $\frac{3}{4}$  inches, and 48 inches in diameter, all by 7 foot 6 inch stroke. Each is provided with 4 gridiron valves worked by independent cams, so made as to equalize the cut-off. The high pressure cylinder only is provided with an adjustable cut-off, ranging from 0 to nine-tenths stroke. This is automatic, and is controlled by a hydraulic governor actuated by a high speed ball governor. Between the high pressure and intermediate cylinders and the intermediate and low pressure cylinders are reheating receivers. The shaft is hollow, 29 feet long, 22 $\frac{1}{2}$  inches in diameter, with a 7 inch hole throughout its length. Its bearings are 22 inches by 40 inches. The shafts, cranks, pins, piston rods, cross heads, and links are made of the finest quality of Krupp crucible steel. The outboard pedestal of the shaft is provided with a ball and socket shaft. The fly wheel is 30 feet in diameter.

The hoisting system is the constant motion non-reversing friction system, the drum rotating with the engine shaft when hoisting and on the shaft when lowering. The hoisting drum is conical, 27 feet in diameter at one end and 14 feet 7 inches at the other, and turned with a spiral groove to accommodate 5,500 feet of 1 $\frac{1}{2}$  inch wire rope. The engine, by means of an automatic device, varies its speed from 30 to 45 revolutions per minute, thus hoisting at a uniform rate. The power is thus varied as more or less rope is to be hoisted. The engine house, which contains also the pumps and accumulators, is 112 feet long by 68 feet wide, and is commanded by a 30 ton traveling crane.

The boiler house is 76 feet by 68 feet. It contains five boilers of the Belpaire type, 90 inches in diameter. They are the largest Belpaire boilers ever built, and weigh 86,000 pounds each. The fireboxes are each 4 feet 7 inches wide inside by 9 feet long, but the last 18 inches are covered by firebrick. A brick arch extends from this wall toward the fire door. There are 201 tubes 3 inches in diameter and 16 feet long in each boiler. The flues from the firebox to the combustion chamber are 3 feet 3 inches long, and the combustion chamber is 4 feet 3 inches long. The total length of the boilers is 34 feet 5 inches, width over all 10 feet 5 inches, and height 9 feet 6 inches. The total heating surface of each boiler is 2,985 feet, and grate surface 68 $\frac{3}{4}$  feet. Ratio, 42:1 to 1. The circular shell is  $\frac{3}{4}$  inch thick, the outer firebox  $\frac{3}{8}$  inch, and the inner firebox  $\frac{1}{2}$  inch thick. Tube sheet  $\frac{1}{2}$  inch thick. All sheets are of Otis steel, of 37,000 pounds elastic limit, and 20 per cent elongation in 15 inches. The working pressure is intended to be 185 pounds per square inch.

These boilers have shown themselves capable of giving out 1 horse power for each 4 square feet of heating surface when driving a compound engine. The Calumet and Hecla Mining Company has in service and ordered 46 of these boilers, 19 of which carry 185 pounds steam pressure, and the remainder 135 pounds.


### Unstable Sand.

A rather remarkable accident is described by Herr Schilling in a recent number of the *Centralblatt der Bauverwaltung*. During the construction of the Neustrelitz and Wamund Railway, a small stream, the Recknitz, some 16 $\frac{1}{2}$  ft. wide by 5 ft. deep, had to be crossed near Laage, and it was determined to span this by an arch. To secure good foundations for the abutments, it was necessary to pass through a stratum of peat 16 ft. thick, below which was found a bed of fine sand, on which the foundation courses were laid. The two excavations were made by driving steel piles around the area to be excavated and then removing soil in the usual way, and the bed of the river was not interfered with in the least. The spaces inclosed measured 28 ft. by 13 ft. each, and the piles were driven 5 ft. into the sand. There was no difficulty in removing the first 10 ft., but after that pumping had to be resorted to, a double suction and force pump being started at each side of the river. In this way another 3 ft. was removed, but to excavate the remaining 3 ft. it was necessary to concentrate all the available pumping plant in one pit, so that the other gradually filled with water up to the river level. Shortly after the masons had started work in the dry pit, the bottom suddenly burst up and the trench became half full of water, which curiously enough did not come from the

river, but from the other trench, as was proved by the level of the water in this pit sinking as it rose in the other. The two pits were 50 ft. apart.

### THE WILZIN AUTOMATIC KNIFE.


The knife represented in the engraving embodies a novel feature designed to win for it much favor. In each end of the handle, connected with the spring by which the blade is held closed, is a little tip or catch, by a slight pressure upon which, as indicated by the arrows at A, the blade flies partly open, and it can then



be fully opened with ease by taking hold of the blade. Those who have broken their finger nails and tried their temper in using knives which were hard to open will appreciate the means thus afforded of obviating the difficulty by simply pressing a catch. The knife is closed by pressing the blade into the handle in the ordinary manner. This invention has been patented in many countries, and the knives are made by the Automatic Knife Co., Middletown, Conn.

### AN IMPROVED HAY SLING.

A device for lifting, carrying, and dumping loads of hay, straw, cornstalks, etc., is illustrated herewith, and has been patented by Mr. Joseph Unterbrink, of Ottawa, Ohio. It is a trip frame latch device to which a series of cords are attached to sustain the load, these cords being suspended from a plate held by any suitable overhead support or carrier to allow the loaded sling to be raised by pulley and rope or other mechanism, and moved over the place where the load is to be dumped, which is effected by simply pulling the latch string. The trip frame is a ring of metal to which are pivotally connected a series of trip arms, whose free ends are adapted to rest on or be retained by a latch



UNTERBRINK'S HAY SLING.

bar pivoted in the frame a little to one side of its center. This latch bar has an arm to which a pull cord is attached, and on one of its faces are eyes into which the free ends of two of the trip arms may be entered. Two other trip arms are adapted to rest at their free ends flat upon the opposite face of the latch. Three of the sling cords have rings at their ends, by which they are adapted to be detachably connected to three of the trip arms, but one of the sling cords is permanently attached to one of the trip arms, so that when the latch is slipped, the weight of the load will cause the cords to turn the trip arms instantly downward, allowing the rings to slip from three of these arms and cause the entire trip frame to be suspended from one sling cord, as shown in one of the views. The load is thus dumped quickly and in substantially the same condition as when loaded in the sling.

### A Heavy Gun.

The first high power breech loading 8 inch rifle made entirely of American steel lately passed a successful test at the Naval Ordnance Proving Ground, at Annapolis. The gun is one of four intended for the cruiser Baltimore. Its forgings are from Bethlehem, and the machining and assembling were done at the Washington Navy Yard. With a sample of brown prismatic powder furnished by Messrs. Du Pont, of Wilmington, Del., a muzzle velocity of 2,129 feet per second was obtained with a 110 pound charge and 15.5 tons pressure. The projectile weighed 250 pounds and its velocity was the highest ever attained by an 8 inch shell in this country. Among other interesting features of the trial were the apparent ease and smoothness with which the enormous force of recoil—amounting to over 100 foot tons—was controlled in the short space of 27 inches, without jar or vibration, by the compact and light carriage on which the gun was mounted. This, says the *Army and Navy Register*, is one of the bureau's hydraulic center pivot carriages, and was constructed at the Washington Navy Yard.

**THE PROPOSED SUSPENSION BRIDGE ACROSS THE HUDSON RIVER AT NEW YORK.**

We illustrate in our present issue the great railroad bridge proposed for erection between the States of New Jersey and New York, crossing the Hudson River near Hoboken and entering New York City. The necessary legislation and authorization for its erection seems in a fair way of being acquired. Should it become an accomplished fact, the city of New York will show to visitors not only the largest bridge in the world, but also, it may safely be said, the two handsomest. It has come to be pretty generally recognized that the cantilever type of bridge is as distinctively ugly as the suspension type is beautiful.

In our illustration on the opposite page we show the comparative sizes of four of the leading bridges now completed and of the proposed Hudson River bridge. Its main span exceeds by 1,150 feet that of the Forth bridge, at present the largest in the world. The same illustration is of interest as showing the appearance of three types of such structures—the arched truss, cantilever truss, and suspension bridge.

The necessity for so gigantic a bridge and the justification for its erection are found in the record of the ferry passengers over the Hudson River ferries. Upon the New Jersey shore a number of railroads have their termini, nearly one thousand trains arriving and departing every day, and it is estimated that about twenty million of their passengers alone cross annually. Besides these, an equal number of other persons are estimated to cross, making a total of over forty millions. Much delay is occasioned by the ice, by fog, and obstacles to navigation in general. The landings at the water front of the city are found inconvenient also. The design is to put the work upon a national basis, and to place its construction and the regulation of its traffic under the supervision of the Federal authorities in the person of the Secretary of War. Connecting two States, it is literally an interstate undertaking, and it will serve as one of the main arteries of travel between the entire West of the country and the metropolis. The privilege of free use for the transmission of postal matter and right of way for government telegraphs is to be ceded in return for the Federal recognition.

The main features of the colossal work may now be summarized. It is to carry six railroad tracks, but is to be built so that four additional ones can be introduced when required. The cost of a double track bridge is estimated at \$9,000,000, of a six track bridge \$15,000,000, while four additional tracks can be provided for at an additional cost of \$1,000,000. Its western terminus in the State of New Jersey is upon the meadows between the Hackensack River and Bergen Hill. It is to pass through this hill by an open cut 100 feet wide. The rock from this cut will give the best possible material for concrete, and will be utilized as such. It will probably provide one-half the material required for the concrete of the towers and anchorages. On the eastern side of Bergen Hill, after the cut has been passed, is the first anchorage. This immense mass of masonry is designed on somewhat novel principles. The prevailing idea in its construction is accessibility. It is chambered so that the cables and the anchor irons within it can be inspected and their condition ascertained at any time.


From this the four great cables will start, each four feet in diameter and made up of steel wires laid parallel, as in the East River bridge. Each cable is to be divided by cross pieces into four quadrants. They are to be compacted into a cylindrical shape, and are to be covered with a sheet steel mantle or envelope of such size as to leave a two inch air space all around them. This will leave them accessible for repairs or examination, while providing ventilation, and is certainly an advance on the old system of wire serving.

At the edge of the river on either side the cables pass over steel suspension piers at a height of 500 feet above the water. These towers are of steel, each including sixteen columns 7 feet in diameter at the bottom and 5 feet at the top. The towers are planned to be erected without false work.

The cables are arranged in pairs, in two planes nearly vertical, one cable in each pair being fifty feet above the other. They are connected in the pairs by diagonal bracing, so as to constitute in themselves a truss that would possess sufficient stiffness for ordinary traffic. As a still further re-enforcement, the roadway is strongly trussed vertically as well as laterally, so that the heaviest locomotive will produce little or no local deflection. Four 16 inch wind cables are arranged to resist side

stress from gales. After passing the eastern anchorage, itself well in the heart of the city, the roadway is carried into New York City, near Fourteenth Street, where a double-decked station is to be erected, giving thirty tracks for arriving and departing trains.

**Section of Cable.**



*Cable for East River Bridge on same Scale.*


Experience teaches that such works are generally made too small for future needs. The size of this bridge is based upon definite considerations. It is believed that a ten track bridge will suffice for 120,000,000 passengers annually, or six times the present traffic. For its construction it is thought that about ten years will be required. A speed of thirty miles an hour is allowed for the trains which are to pass over it.

The following tabular statements are of interest. It will be seen that the cost of the bridge proper will represent less than half the total expenditure required for the approaches and stations.

**COMPARATIVE DIMENSIONS OF THE EAST RIVER AND HUDSON RIVER BRIDGES.**

	Brooklyn Bridge.	Hudson River Bridge.
Length, including anchorages.....feet..	3,700	6,500
Height of anchorages....."	85	210
Weight of each anchorage..... tons..	60,000	660,000
Length of each land span.....feet..	930	1,500
Length of middle span....."	1,600	*2,850
Size of towers at high water....."	140 by 59	340 by 180
Height of towers from high water....."	272	500
Height of tower from the deepest foundation to top.....feet..	350	600
Width of bridge....."	85	86
Height above high water....."	135	over 135
Length of one cable....."	3,580	6,100
Number of cables.....	4	4
Finished diameter of cable.....inches..	15 1/2	48
Number of railroad tracks.....	2	6 to 10
Grade on bridge.....per cent..	3 1/4	1 1/2
Weight of iron and steel in the structure.....tons..	6,750	60,000
Allowable speed of trains.....miles per hour..	10	30
Cost from anchorage to anchorage, exclusive of land damages.....	\$5,600,000	\$16,000,000

\* In the clear.



**DETAIL OF TOP OF TOWER OF HUDSON RIVER BRIDGE.**

**ESTIMATE OF COST.**

The Hudson River Bridge, including the anchorages, 6,500 feet long.....	\$15,000,000
The approaches of stone and iron and the connecting railroad switch yards, engine houses, the grand terminal station building and appurtenances.....	11,000,000
Right of way, interest during construction, and incidentals.....	14,000,000
<b>Total cost.....</b>	<b>\$40,000,000</b>

The bill authorizing the construction of this bridge has passed the House of Representatives and is now awaiting action in the Senate.

**A German Salmon Trade.**

The duty imposed by Germany is equivalent to 10 cents per pound on canned salmon. The fish in a natural state may be imported duty free.

It is proposed to catch the salmon on the Columbia; the fish to be cut in two pieces and then packed in salt, thirty pounds of salt to one hundred pounds of salmon; the fish then must lie four days in the salt and then must be placed in cold storage for two weeks, then it must be shipped to Germany. The salmon must weigh twenty pounds each, as any smaller fish would become so thoroughly impregnated with the salt that it would be impossible to freshen them. A good sized salmon, it is claimed, can be made as fresh as it was the day it was taken from the river.

It is said the agent of a German house has already made contracts with a number of canners, agreeing to take all the salmon they can furnish on the above terms, cleaned fish, at six cents per pound, on the Columbia River.

With our facilities of refrigerator cars it would seem as if our Eastern markets ought to be supplied with fresh salmon at comparatively low prices.

**The Pension Epidemic.**

He who makes two pension claims grow where only one grew before is not entitled to the same blessing as the man who makes two blades of grass spring up where only one gladdened the eye before, but such an individual is at least sure of a hearing. I have wondered often, says a writer in the *Christian Union*, why some of the absurd claims for pensions were not outdone by demands for the government bounty on the part of men who did incidental service during the war in guarding Washington. These men were clerks in the various departments, and, when the Confederates menaced Washington, in 1864, were called upon to drill, to do guard duty, and to perform other soldierly duties, though not sworn into the service. Odds and ends of uniforms were issued these extemporized companies, and some ludicrous effects in attire were the result. I remember, the writer adds, that the trousers assigned me had one leg three inches shorter than the other, and I have often felt that the wear and tear of feeling I suffered because of my diversified appearance ought to warrant my application for what I would call a pensionette. It might well take the form of a gift of the price of a pair of trousers, the two legs whereof were of equal length, and the payment be made on the installment plan.

**Great Guns for Russian Forts.**

The largest gun yet manufactured at Krupp's works at Essen, which is intended for the naval fortifications at Cronstadt, is made of the finest quality of cast steel and weighs 270,000 pounds (about 135 tons), the caliber is 16 1/4 inches, and the barrel 44 feet long, the core having been removed in one piece. The greatest diameter is 6 1/2 feet, and the range about twelve miles. It will fire two shots per minute, each estimated to cost £300. At the trial the projectile, 4 feet long and weighing 2,600 pounds, was propelled by a charge of 700 pounds of powder and penetrated 19 inches of armor, going 1,312 yards beyond the target. It was carried from Essen to Hamburg on a car specially constructed for the purpose. Work is reported as now being pushed forward on several guns of this class, and a number of smaller ones have recently been ordered.

**STEEL PIPES.**—Steel pipes as a substitute for cast iron now form an important item for the engineer's consideration in the conveyance of water. Such pipes are being adopted for several reasons. As their weight is only about one-quarter the weight of cast iron pipes for the same service, the matter of transportation forms an important consideration. They are also much less liable to fracture than cast iron.




**The Traveling Salesman.**

A mill furnisher asked the *Modern Miller* recently if the editor could recommend a thoroughly competent man for a traveling agent who did not "bum" around saloons. He said he had become heartily sick of the bumming element among machinery men, and "wanted to secure *one* man, if such a thing were possible, whose expenses would not exceed all the profits on the ma-


chines he sold." This mill furnisher has, perhaps, been more than usually unfortunate in his efforts to secure the right kind of men to represent him, but he certainly echoes the sentiments of the majority in regard to that class of men who seem to find it necessary to open a beer barrel or a keg of whisky in every town they visit. It is getting to be a great nuisance. No sensible employer asks or expects an agent to carry a "Sunday

school card" around with him, but he does expect that he will not disgrace himself or the house he represents.


THE medal of the Astronomical Society of the Pacific has been awarded recently to Wm. R. Brooks for his discovery of a comet on March 19, 1890. It is the first medal issued by the society.




THE PROPOSED HUDSON RIVER BRIDGE AT NEW YORK CITY.




St. Louis Bridge over Mississippi River.




Poughkeepsie Bridge over Hudson River



Forth Bridge in Scotland



New York-Brooklyn Bridge over East River.



SPANS.  
1500—2850—1500 feet.  
FOR SIX TRACKS.

**Explosive Substances.**

BY CHARLES D. LIPPINCOTT.

The following paper was, says *The Pharmaceutical Era*, read before the Pennsylvania Pharmaceutical Association at its meeting in 1886.

SECTION FIRST.—*a. Substances which explode when triturated singly.*—Under this head are to be found only a limited number, among which are :

1. Potash chlorate (commercial), under sharp concussion.
2. Mercury fulminate, explodes with green flame.
3. Mercury nitric oxide.
4. Copper nitrate, dry.
5. Copper fulminate.
6. Antimony fulminate.
7. Gold fulminate.
8. Silver fulminate.
9. Glonoin (nitroglycerine).
10. Hydrogen chloride.
11. Nitrogen iodide.
12. Nitrogen chloride.

The latter three substances and the fulminates are among the most violent of the explosives, their chemical stability being very light.

It may be well to state that in substances which contain carbon, oxygen, and nitrogen, the latter in a more or less feeble state of combination with the whole or part of the oxygen, when the explosion takes place the N parts with its O, which combines with the C, forming CO<sub>2</sub> and CO with generation of heat, and N is set free.

If H be present in the explosion, H<sub>2</sub>O is formed in the form of greatly expanded vapor. When Cl is present, it takes the part of the N as from potash chlorate.

We find that nitro substitution for H forms very dangerous explosive compounds, as glonoin, a tri nitro product, also xyloidine, a bi nitro, and last, but not least, nitro mannite, a product from manna sugar, and containing six molecules of nitric peroxide (N O<sub>2</sub>) associated with the carbon of the sugar.

*b. Substances which explode when mixed with other substances and triturated :*

1. Potash chlorate with acid tannic.
  2. Potash chlorate with sulphur.
  3. Potash chlorate with antimony sulphuret.
  4. Potash chlorate with pot. nit. and ammon. phosphate.
  5. Potash chlorate with picrate of ammonia.
  6. Potash chlorate with am., sulph., copper and soda hyposulphite.
  7. Potash chlorate with picrate of potash produces purple flame.
  8. Potash chlorate with picric acid, yellow flame.
  9. Potash chlorate with acid oxalic, detonates violently.
  10. Potash chlorate with potash permanganate, detonates.
  11. Potash chlorate with sulphur and iodine, violent detonation.
  12. Potash chlorate with antimony sulphuret.
  13. Potash chlorate with sulphur and fulminate of mercury (very sensitive).
  14. Potash chlorate with potash prussiate and sugar.
  15. Potash chlorate with ammonio sulphate of copper.
  16. Potash chlorate with soda hyposulphite, fuses and deflagrates.
  17. Potash nitrate, dry carbonate of potash and sulphur.
  18. Potash permanganate and tannin, deflagrates.
  19. Potash permanganate and picric acid, violent detonation.
  20. Potash permanganate, picric acid, and tannin, violent detonation, with yellow flame.
  21. Potash permanganate and potash picrate (loud).
  22. Potash permanganate, potash picrate, and tannin, very loud.
  23. Potash permanganate and potash oxalate.
  24. Potash permanganate, potash oxalate, and tannin, violent.
  25. Chloride of lime and iodine and iodine resub. (detonates).
  26. Dry nitrate of copper and oxalate of potassa, with tannin acid, explodes.
  27. Antimony sulphuret, acid picric, and potassa chlorate, detonates with flash.
  28. Amorphous phosphorus, acid tannic, acid picric, potassa chlorate, potash permanganate (very sensitive, flashes without detonation).
  29. Manganese black oxide, picric acid, permanganate of potash, flash, no detonation unless confined.
  30. Potassa bichromate, tannin, and picric acid (orange red flash).
  31. Potassa bichromate, tannin, picric acid, and amorphous phosphorus, red flash.
  32. Ammonium picrate, potassa nitrate, powdered charcoal. Nitric acid with this combination one part, ammonium picrate two parts, and potassa nitrate three parts, forms what is known as *picric powder*.
- The following are a few explosive mixtures brought into closer or more compact union by the solvent power of a suitable menstruum ; certain component parts, however, remaining in suspension.

33. Indigo, acid tannic, potash chlorate, and amorphous phosphorus, diluted alcohol q. s. to form paste, when dry, is violently explosive, giving off a volume of white smoke.

34. Soda chlorate with golden sulphuret of antimony, very sensitive, emits crackling sounds.

35. Lamp black, amorphous phosphorus, strontia nitrate, tannic acid, spts. turpentine, to form paste, detonates with red flash and white smoke.

36. Substitute dry ammonia, sulphate of copper or dry cupric oxide, for strontia, a beautiful blue flash with loud report results.

37. Starch or dextrine..... 10 parts.  
Potash chlorate..... 20 "  
Amorphous phosphorus..... 5 "  
Water..... 8 "

Mix. When dry produces loud detonation, if confined, evolving copious white smoke.

38. Acid sulphuric..... 75 parts.  
Acid nitric..... 30 "  
Simple sirup..... 20 "

This mixture is known by name of "Vigorite."

39. Another composed of vigorite, nitrate of potash, and cellulose, is known by the name of "Nitroline."

These two compounds are dangerously explosive.

40. Lac sulphur, golden sulphuret of antimony, valerianate of zinc, chlorate of potassa. This combination has been prescribed and has exploded.

41. Iodine fulminates with turpentine and most of the hydrocarbon volatile oils.

Any of the nitrates will form explosive mixture with combustible substances.

The chlorates, however, part with their O more easily than the nitrates, and in consequence of the strong affinity of chlorine for the metals, chlorine mixtures are very sensible to friction and percussion.

In explosive compounds the elements are all in chemical combination ; presenting a definite explosive molecule (*i. e.* containing both combustible and supporter of combustion) ; hence we can readily understand how an explosive compound is more sudden and violent than that of the most intimate mechanical mixture.

Potassium chlorate and all the other chlorates should never be prescribed in powder, mixed with organic and inorganic, combustible, or oxidizable bodies. They should, therefore, when combined, be prescribed only in solution.

The following prescriptions have been known to explode and are dangerous.

℞ Potassa chlorate.  
Sodium or calcium, hypophosphite.  
Aqua. M.

The two salts should be dissolved separately.

℞ Potassa chlorate.  
Acid tannic.  
Glycerine.  
Aqua.

This should be prepared by making a solution of the tannin in the glycerine and potassa chlorate in the water.

℞ Potassa chlorate.  
Pulv. catechu. Should not be dispensed.

℞ Potassa chlorate.  
Pulv. gallæ or acid tannic.

SECTION SECOND.—*Substances which undergo or are liable to spontaneous combustion.*—Under this head we find that all compounds that contain oxygen and chlorine, feebly combined with carbon, are liable to undergo spontaneous combustion, by the elimination of O or O and Cl, causing the generation of sufficient heat to inflame the C.

The following comprise those which I have found by experiment and research to undergo this change.

1. Silver oxide and creosote.
2. Potassium permanganate and glycerine. (Spontaneously deflagrates.)
3. Potassium permanganate and acid oxalic. Fuses and deflagrates.

The following prescriptions, under this head, are dangerous ; all of which have exploded spontaneously ; hence should not be handled by empirical manipulators.

4. ℞ Potassa chlorate.  
Tr. chlor. iron.  
Glycerine. If warm, will explode.
5. ℞ Potassa permanganate.  
Alcohol.  
Aqua distil.

This may be dispensed by adding the potassa slowly to the alcohol and water previously mixed, and by dispensing in a loosely stoppered vial.

6. ℞ Oil amber.  
Acid nitric ; explodes with penetrating odor resembling musk.

7. ℞ Oxide of silver.  
Muriate of morphia.  
Extract of gentian.

8. ℞ Oil turpentine.  
Acid sulphuric.

Should be mixed gradually in an open vessel, as this has caused violent explosions and serious accidents.

9. ℞ Acid chromic.  
Glycerine.  
May be combined by adding the acid by degrees, rubbing slowly.

10. ℞ Iodine.  
Spts. camphor.  
Camph. soap liniment.  
This evolves nitrogen iodide.

11. ℞ Acid nitric.  
Acid muriatic.  
Tinct. nux vomica. (Explodes in two hours.)

12. ℞ Potassa sulphate.  
Aqua rose.  
Tinct. benzoin.

13. ℞ Soda borate.  
Soda bicarb.  
Glycerine.  
Water.

Evolves CO<sub>2</sub>, therefore explodes when corked too tight.

In general those mixtures that give off gas should not be corked until the evolution of gas is over. In evidence of the action of the rapid evolution of O in contact with any combustible substance, especially any volatile or inflammable substance, the following affords a good example :

Take of sulphuric acid one fluid drachm, permanganate of potash fifteen grains. Mix in a small mortar. By dipping a glass rod in this solution and touching it to a small quantity of cotton, previously saturated with alcohol, the latter will immediately take fire.

**Tobacco.**

The amount of tobacco annually consumed in the United States is estimated by an apparently competent authority at 310,000,000 pounds. Seventy million pounds are utilized in the production of domestic cigars ; 222,000,000 pounds of chewing and smoking tobacco are consumed ; 8,000,000 pounds are used in the manufacture of snuff ; 6,000,000 pounds are required in the production of cigarettes ; and 4,000,000 pounds of cigars are imported. This would make an average annual consumption of five pounds for every person in the country. But as not more than one-fifth of our population use tobacco, it follows that those who do, consume, on an average, twenty-five pounds each per annum. Opinions differ as to whether this article should be designated a luxury or a necessity. In speaking of the cost of the tobacco habit, an exchange says :

If the tobacco users of the United States would abstain for a period of two years from the chewing, smoking, and snuff-taking habit, and place the money they would spend for tobacco in that period in a common fund, there would be enough money in the fund to almost wipe out the entire national debt, and five years abstaining would give the head of each family in the United States enough money to invest in an eighty acre homestead farm in the far Western States and Territories ; or it would give us a navy of fifty first-class war vessels, fully equipped, and create a fund that would man and maintain them and the Navy Department for a period of at least twenty-five years.

It can thus be seen what is the magnitude of the tobacco trade of the United States, and what a multitude of devotees are willing to pay annually for a habit which gives them so much consolation and comfort, if nothing else.—*The Price Current.*

**American Universities.**

Owing to the great territorial extent of this country, its work in the direction of higher education has taken a peculiar phase. Instead of concentrating itself upon the formation of a few colossal colleges, a great number of smaller institutions have been founded all over the land. This has had an excellent effect in freeing higher education from the traditions of two or three great universities. On the other hand, it is claimed that these smaller institutions are of too low a grade. Recently a movement has been discernible in the same line which has taken the form of re-enforcing the colleges by universities. These are now becoming quite numerous and are of the highest grade. Johns Hopkins University, in Baltimore, the Clark University, in Worcester, Mass., the Stanford University, at Palo Alto, Cal., and a number of denominational universities, all consecrated to post-graduate studies, threaten to give a new aspect to American education. Work has already been done that has won credit for American science everywhere, and more is in the future. The late President Barnard, of Columbia College, was well in accord with this movement, and it is said desired to make his college a post-graduate university. It is certain that for the next generation a liberal education in American institutions will have a far higher meaning than it has had hitherto. The efforts of England and the Continent in the development of the intellectual life of their people, creditable as they are, may yet find a formidable rival here



**The Persecuted Chinaman.**


We add our protest to others against the Chinese census bill which has passed the House of Representatives, and is now pending in the United States Senate. This bill requires the Superintendent of Census to give to every Chinaman in the country a certificate, which, after ninety days from the date of the beginning of the enumeration, shall be the sole evidence of his right to remain in the United States, and in the absence of which he shall be liable to deportation or to imprisonment for five years. We are glad to see that the committee of the Senate proposes to omit the clause making the right of a Chinaman to remain in this country dependent upon the certificate. But this is only a mitigation of the wrong threatened by this bill. We do not deny the right of the nation to sift out, or even to exclude by proper legislation, immigrants whose coming the nation believes to be dangerous to its well-being. But, the *Christian Union* says, to select a certain class who have come, and put them under special restriction and requirements and render them subject to exile from the land of their adoption for no crime whatever, is an act wholly unjustifiable and wholly unworthy a great nation. It is difficult, indeed, to conceive even a specious argument for such legislation.

**The Action of Water at High Temperatures and at Great Pressures upon Wood and Cellulose.**

Pure cellulose gives traces of sugar at the ordinary pressure. At higher pressures the quantity of sugar increases, but at 20 atmospheres it is converted into hydrocellulose. Wood is attacked by water at the ordinary pressure, but the action reaches its maximum at 5 atmospheres, when beech wood loses 26.7 per cent of its weight, of which 11 per cent becomes sugar. There are also produced dextrines, precipitable by alcohol. No vanilline is obtained from the aqueous or ethereal extracts, or from the dried residues. The color reactions of Ihl must be due to the transformation of lignine into carbohydrates.—*H. Tauss (Dingler)*.

**AN IMPROVED GRINDING MACHINE.**

The accompanying illustration represents a machine specially designed for grinding razors and similar articles concave or hollow. It has been patented by Mr. George J. Ridley, of No. 146 Wall Street, Auburn, N. Y. In the top crossbeam of the frame is a bearing supporting a vertical shaft, on which is a grinding wheel with curved periphery. Directly opposite this wheel is a second grinding wheel, the shaft of which is mounted to turn in suitable bearings on a block adapted to slide on the top crossbeam of the frame, toward or from the other wheel. The block is moved with a screw, and is locked in place when adjusted by bolts extending downward through a slot in the top crossbeam. On the upper ends of the shafts carrying the grinding wheels are pulleys, over which passes a belt, also passing over a large pulley on the upper end of a rear vertical shaft, motion being communicated to the latter shaft by a bevel gear and pinion from a transverse shaft operated by cranks connected with treadles. A seat is located in front of the machine in such a man-




**RIDLEY'S GRINDING MACHINE.**

ner as to enable the operator seated thereon to conveniently actuate the treadles and hold the articles to be ground in contact with the wheels. The small figures represent the adjustment of the wheels for grinding razors concave or hollow. By removing the treadles and attaching a pulley the machine may be run by power, when, by using a drip to keep the steel from heating, work may be done with great rapidity.

**AN IMPROVED STEAM ENGINE VALVE.**

An automatic valve mechanism for steam engines, designed to be operative without the use of an eccentric or crank, is shown in the accompanying illustration, and has been patented by Mr. William Gehring, of the Standard Iron Works, San Diego, Cal. Fig. 1 is a side view of the valve-operating piston, and



**GEHRING'S VALVE FOR STEAM ENGINES.**

Fig. 2 a longitudinal section of the cylinder and valve chest, Fig. 3 being a view in perspective showing the application of the improvement. A steam chest on top of the cylinder covers the valve seat, and is provided with a cylinder in which slides the valve-operating piston. The valve seat has an exhaust port, and steam ports which communicate with the ends of the cylinder. To the valve seat is fitted a double main valve, in the back of which is a cavity for receiving an arm on a shaft extending through the side of the valve chest, and provided with a starting lever. The valve-operating piston has a central mortise for receiving the rectangular back of the main valve, and in the heads of the piston are diagonal passages through which steam is admitted to spaces at each end of the steam chest. In the lower part of the valve cylinder are live steam ports and exhaust ports. In the top of the main cylinder, underneath the exhaust ports in each end of the valve cylinder, is a valve casing with a spring-pressed tappet valve, whose stem extends into the path of the power piston, the latter having beveled ends for engaging these valve stems as the piston nears the end of its stroke in either direction. By this arrangement the tappet valves are operated to admit steam to the space at the ends of the valve-operating piston. This valve mechanism, though applicable for general purposes, is particularly designed for use in connection with steam pumps.

**Synthetic Indigo.**

A new and very simple method of synthesizing indigo has been discovered by Dr. Flimm, of Darmstadt (*Berichte*, No. 1, 1890, *Science*). In studying the action of caustic alkalies upon the monobromine derivative of acetanilid  $C_6H_5NH.CO.CH_2Br$ , a solid [melting at  $131.5^\circ$ ], it was found that when this substance was fused with caustic potash, a product was obtained which at once gave an indigo blue color on the addition of water, and quite a considerable quantity of a blue solid resembling indigo separated out. The best mode of carrying out the operation, according to *Nature*, is described by Dr. Flimm as follows:


"The monobrom acetanilid is carefully mixed with dry caustic potash in a mortar, and the mixture introduced into a retort and heated rapidly until a homogeneous reddish brown melt is obtained. This is subsequently dissolved in water and a little ammonia or ammonium chloride solution added, when the liquid immediately becomes green, which color rapidly changes into a dark blue, and in a short time the blue coloring matter is for the most part deposited upon the bottom of the vessel in which the operation is performed. The fused mass may also conveniently be dissolved in dilute hydrochloric acid and a little ferric chloride added, when the formation of indigo takes place immediately. The collected blue coloring matter may be readily obtained pure by washing first with dilute hydrochloric acid, and afterward with alcohol."

That this blue substance was really common indigo was proved by the fact that it yielded several of the most characteristic reactions of indigotin, such as solubility in aniline, paraffin, and chloroform; its sublimation; and the formation of sulphonic acids, which gave similar changes of color with nitric acid to those of indigotin. The final proof was afforded by its reduction to indigo white and reoxidation to indigo blue by exposure to air. Moreover, the absorption spectrum


of the coloring matter was found to be identical with the well known absorption spectrum of indigo; hence there can be no doubt that indigo is really formed by this very simple process.

**AUTOMATIC TIME AND DATING STAMPS.**

A small compact instrument which is an effective watchman's time clock, and by means of which, by the simple pressure of the hand, the time, date, names, and other designations may be instantly recorded or printed on documents and papers, forms the subject of a patent recently issued to Mr. Charles Stahlberg, of Brooklyn, N. Y. This instrument requires no attention except winding once a week, the month, date, and time of day, to the fraction of a minute, being set automatically at the proper second, including the automatic setting of the first day of a new month from a long or short month, and February of a common or leap year. It is in fact an automatic perpetual calendar, which indicates on paper at any moment the year, month, day, hour, and minute of time on which it is used. The type wheels of the instrument have on their periphery the type corresponding to the divisions of time which each one is intended to print—first, the year wheel; second, the meridian and hour wheel operating mechanism; third, a meridian wheel; fourth, a minute wheel; fifth, a minute wheel operating mechanism; sixth, an hour wheel; seventh, a date wheel operating mechanism; eighth, a date wheel; ninth, a month wheel; and finally, a month wheel operating mechanism. The clock movement is constructed to move the shaft which actuates the type wheel mechanism equal distances at intervals of one minute, or at such intervals as is desirable, the shaft being stationary during the intervals, the intermittent motion of the actuating shaft being gained by the interposition of an auxiliary motor or spring in the train of the clock. This really divides the clock train into two portions, the lower portion of the train being driven by the main springs of the clock, and its office being to wind the auxiliary motor spring once a minute. By this means the power driving the time movement is equalized every minute, and the clock is run under the best possible conditions for the attainment of accuracy. The inking ribbon and mechanism necessary for adjusting it are attached to the hinged cover of the case, giving ready access thereto when the cover is turned back. To guard against picking the lock which opens the stamp, means are supplied to attach a seal. The mechanism, being automatic, can be placed in connection, electrically or otherwise, in



**NEW TIME STAMP-CLOSED.**



**NEW TIME STAMP-OPEN.**

police, messenger, and telephone service, with stock tickers, etc., and wherever it is desirable to keep an exact record of date and time to the minute. It is one of the most reliable and effective devices that has come under our notice. The instruments are furnished by the Accurate Time Stamp Co., No. 431 Eleventh Avenue, New York City.

The question of the best form of meter for registering the supply of electricity to private consumers is being argued in English electrical circles.

RECENTLY PATENTED INVENTIONS.

Engineering.

**SLIDE VALVE.**—Edward Leslie, Orangeville, Ontario, Canada. This invention consists of an outer valve having a loose top plate and an inner valve having play in the outer valve, and provided with top ridges on which rests the top plate, the valve being designed to permit of being run at a high rate of speed, and prevent the unseating of the outer valve.

Railway Appliances.

**CAR COUPLING.**—Martin L. Mardis and John W. Britton, New Lisbon, Ohio (H. Morrow, admr. of John W. Britton, deceased). In this coupling, in combination with a link-securing hook, is a lock bar movable into position to hold the link in engagement with the hook, and a shaft movable longitudinally and connected with the lock bar, with other novel features, whereby the coupling and uncoupling may be effected from either side of the car.

**STOCK CAR.**—Christopher B. Herman, Norwich, Kansas. This car has a central row of posts, with gates hinged thereto, a longitudinal foot board upon the top of the posts, and braces extending therefrom to the roof of the car, with flexible partitions and other novel features, designed to promote convenient loading, the proper balancing of the load, and the feeding and watering of the stock, and insure its general comfort.

**ELECTRIC RAILWAY TROLLEYS.**—Franklin C. Wheeler, St. Joseph, Mo. This is an attachment of a tube with a weight, and having a detent for holding the weight in elevated position, a chain or cord being connected with the weight and with the trolley, so that when the trolley jumps from the conductor it will release the weight, thus drawing down the trolley so that it will not come in contact with the upper work and injure the supports of the conductor.

Mechanical.

**WABBLE SAW.**—Lewis B. Rogers, Mount Vernon, N. Y. This invention is designed to provide a cheap and efficient construction whereby the angle of the saw may be quickly changed and fixed, two bolts being so arranged that one will fit loosely in a hole in the saw plate and bear against the adjoining collars, while the other is screw-threaded and fits a corresponding thread in the saw plate, by means of which the saw is adjusted.

**SPRING BENDING MACHINE.**—Sobieski L. Bond, Charleston, S. C. Combined with a block adapted to slide transversely is a pair of tongs having two pivoted prongs, one pivoted on the block and the other adapted to press the spring on to the block, with other novel features, the bending taking place while the springs are red hot, and the machine being designed to quickly and accurately bend and set springs to the proper shape.

**TRY SQUARE AND PROTRACTOR.**—Franklin E. Roberts, Flint, Mich. This is a combination instrument, in which the try square has separate and independent quadrants movably secured to its two members and adapted to be projected beyond the edges, the instrument being capable of many and varied uses by carpenters, millwrights, car builders, draughtsmen, etc.

Agricultural.

**HAY RAKE AND SHOCKER.**—Wilbur S. Winkle, Indian Creek, West Va. This invention covers various novel details and combinations of parts in a machine designed to be completely under the control of the driver, whereby the hay may be expeditiously and cleanly gathered and delivered without waste to a shocker and packed therein, while the shocker may be quickly dumped and the hay conveniently delivered restored to its upright position.

**LAND LEVELER.**—John N. Holland, Pueblo, Col. This is a machine more especially adapted for use on such lands as are farmed by irrigation, and has a frame with transverse scrapers at front and rear and a pair of crank axles with running wheels, one at the front and the other at the rear, with a connecting rod and a lever for operating them simultaneously to raise and lower the frame.

**RICE HULLER AND POLISHER.**—William S. Mallard, Darien, Ga. Combined with a motor is a revolving shaft on which are arranged a series of separately adjustable plates, arranged adjustably in spiral form on the shaft, whereby the pressure and friction can be regulated to remove the outer hull, and also the cuticle or inner skin, and polish the rice.

Miscellaneous.

**KETTLE SUPPORTER.**—Jacob M. Rohm, Gapsville, Pa. This an adjustable device designed to conveniently support a kettle over a fire, and whereby heavy and large kettles may be raised or lowered while in use as desired, the invention also providing for the support of two or more kettles, and permit of their safe lifting or lowering, as well as their lateral adjustment.

**INK ERASER.**—William L. Gundlach, Lake Mills, Iowa. This is a device consisting of a double tubular reservoir, in the shape of a pencil, adapted to contain a solution of chlorinated lime in one compartment of the tube and an acid in the other part, whereby the fluid can be applied exactly where it is wanted, and without any excess, to erase one letter of a word or more.

**BLIND.**—Thomas E. Armitstead, Mazomanie, Wis. This invention covers a novel construction and combination of parts whereby, when the slats are closed, the lower rabbet of the upper slat is brought in contact with the upper rabbeted surface of the next slit below, so that when the blinds are closed their outer faces will be in the same vertical plane, the outer faces of the slats also being in the same vertical and horizontal plane as the outer face of the blind frame.

**INK WELL ATTACHMENT.**—Dennis B. McAlice, Lincoln, R. I. This is a device for use in the wells of inkstands to supply the pen as it is dipped with a given quantity of ink, and consists of a buoyant pen dip having a hollow air-tight and tubular upper portion, with separated side pieces connecting with the bottom of the cup, whereby the pen will always be supplied with pure ink, but can never take too much.

**SAFETY LATCH FOR ELEVATOR DOORS.**—John Johnston, New York City. This invention consists of a beaded latch bar eccentrically pivoted, with teeth on its under edge below the pivotal point, a rack engaging with the teeth of the latch bar, and a bow spring contacting with one end of the rack, whereby the car by its movement will automatically unbolt the door, and will automatically lock a closed door.

**METALLIC PLATE FOR BOOTS OR SHOES.**—Edward Duerden and Joseph Cheetham, Iemilovo, near Moscow, Russia. This is a rotatable annular metallic heel plate, with a filling of leather or other like wearing material arranged within a space between two plates, so constructed as to be supported and secured to the heel of the boot or shoe.

**RECLINING CHAIR.**—Louis Goetel, New York City. This is a chair in which the back may be made to incline at any desired angle, the invention covering various novel features and combinations of parts whereby the movements of the back may be regulated by the occupant without arising from the chair.

**SHOWER BATH, ETC.**—Heinrich Schaffstadt, Giessen, Germany. By this invention a water pipe is provided with the usual spray nozzle and outlet faucet, while a steam pipe extends through the water pipe to heat the water, the steam passing in an opposite direction to that from which the water flows, whereby the water for the bath may be heated to any desired temperature.

NEW BOOKS AND PUBLICATIONS.

The *Illustrated American* maintains the high standard of excellence shown in its first number. The purely American character of this magazine entitles it to a place in every family. The photographic reproductions of places and houses of historical association render it of special interest. Some excellent character sketches of members of the United States Senate and House were given in last week's issue. Subscription, \$10 per year, should be sent to M. M. Minton, general manager, Bible House, Astor Place, New York city.

SCIENTIFIC AMERICAN BUILDING EDITION.

APRIL NUMBER.—(No. 54.)

TABLE OF CONTENTS.

1. Elegant plate in colors of a residence on Long Island, N. Y., built from plans prepared by Munn & Co. Cost about \$6,500. Perspective elevation, floor plans, details, etc.
2. Colored plates, details, and suggestive floor plans for a residence at Buffalo, N. Y., built at a cost of \$7,000.
3. Illustrations of an attractive cottage at Excelsior Springs, Mo., erected at a cost of \$1,300 complete.
4. A residence at Park Hill, South Yonkers, N. Y., erected at a cost of \$8,500. Perspective and floor plans.
5. Perspective elevation and floor plans of a residence recently erected at Belle Haven, Conn., at a cost of \$11,000. McKim, Mead & White, New York, architects.
6. Engraving of a Binghamton, N. Y., cottage. Cost \$4,950 complete. Floor plans and perspective.
7. Elevation and floor plans of a brick cottage. Cost about \$5,000.
8. A double dwelling costing \$5,200, built at Portchester, N. Y. Perspective and plans.
9. View of an economical water tower at Hill View Park, South Yonkers, N. Y.
10. A cottage at Mountain Station, N. J., from designs by F. W. Beall, architect, New York. Cost complete \$8,000. Plans and perspective.
11. Two carriage houses. Cost about \$1,500.
12. Two pages of illustrations showing in general view and detail the wreck of the tower of the Church of the Covenant, at Washington, D. C., which fell when nearly completed on August 22, 1888.
13. A Crescent Place, South Yonkers, N. Y., residence, recently erected at a cost of \$7,500. Plans and perspective view.
14. Miscellaneous Contents: Concrete arches.—Dwarf canals.—Water works for small towns.—Soft stone.—Brick pavements.—Fall of the tower of the Church of the Covenant, Washington, D. C.—Improved duplex plumb and level, illustrated.—Improved anti-friction hanger for sliding doors, etc., illustrated.—Wood's pedal valve for radiators, illustrated.—An improved turnbuckle, illustrated.—Improved copying press, illustrated.—The Wing disk fans, etc.—Mortising and Tenoning machine, illustrated.

The Scientific American Architects and Builders Edition is issued monthly. \$2.50 a year. Single copies, 25 cents. Forty large quarto pages, equal to about two hundred ordinary book pages: forming, practically, a large and splendid MAGAZINE OF ARCHITECTURE, richly adorned with elegant plates in colors and with fine engravings, illustrating the most interesting examples of Modern Architectural Construction and allied subjects.

The Fullness, Richness, Cheapness, and Convenience of this work have won for it the LARGEST CIRCULATION of any Architectural publication in the world. Sold by all newsdealers.

MUNN & CO., PUBLISHERS, 361 Broadway, New York.

Business and Personal.

The charge for insertion under this head is One Dollar a line for each insertion; about eight words to a line. Advertisements must be received at publication office as early as Thursday morning to appear in next issue.

For Sale—New and second hand iron-working machinery. Prompt delivery. W. P. Davis, Rochester, N. Y. Acme engine, 1 to 5 H. P. See adv. next issue.

Presses & Dies. Ferracute Mach. Co., Bridgeton, N. J. Turck water motors at 12 Cortland St., New York.

For steel castings of best quality, write the Buffalo Steel Foundry, Buffalo, N. Y.

Best Ice and Refrigerating Machines made by David Boyle, Chicago, Ill. 140 machines in satisfactory use.

The Improved Hydraulic Jacks, Punches, and Tube Expanders. R. Dudgeon, 24 Columbia St., New York.

Safety Elevators, steam and belt power; quick and smooth. The D. Frisbie Co., 112 Liberty St., New York.

Veneer machines, with latest improvements. Farrel Fdry. and Mach. Co., Ansonia, Conn. Send for circular.

Tight and Slack Barrel Machinery a specialty. John Greenwood & Co., Rochester, N. Y. See illus. adv., p. 173.

Screw machines, milling machines, and drill presses. The Garvin Mach. Co., Laight and Canal Sts., New York.

For Sale—A valuable patent feed water heater and condenser. Address J. Willenbrink, New Richmond, O.

Guild & Garrison, Brooklyn, N. Y., manufacture steam pumps, vacuum pumps, vacuum apparatus, air pumps, acid blowers, filter press pumps, etc.

Linen and rubber hose, all kinds of belting, general mill and factory supplies. Send for catalogue and prices. Greene, Tweed & Co., 33 Chambers St., New York.

The Holly Manufacturing Co., of Lockport, N. Y., will send their pamphlet, describing water works machinery, and containing reports of tests, on application.

The best book for electricians and beginners in electricity is "Experimental Science," by Geo. M. Hopkins. By mail, \$4; Munn & Co., publishers, 361 Broadway, N. Y.

Wanted—To purchase the patent or right to manufacture an article that is useful, practical, and calculated to come into general use, requiring a moderate capital to manufacture. W. L. Elder, 43 S. Meridian St., Indianapolis, Ind.

Wanted—Foreman for machine shop in large city in Wisconsin, employing about 100 men. One posted on Corliss engines and ice machines and who understands German preferred. Address Foreman, care Scientific American, New York.

Superintendent wanted by a large manufacturing concern in a large center, working iron and wood, chiefly the former. Must be a thoroughly educated mechanic and a draughtsman, energetic, experienced, and competent to handle large numbers of men. Young man preferred. Give full experience, references, and age. Address "Superintendent," care Scientific American, N. Y.

Send for new and complete catalogue of Scientific and other Books for sale by Munn & Co., 361 Broadway, New York. Free on application.

Notes & Queries

HINTS TO CORRESPONDENTS.

Names and Address must accompany all letters, or no attention will be paid thereto. This is for our information, and not for publication. References to former articles or answers should give date of paper and page or number of question. Inquiries not answered in reasonable time should be repeated; correspondents will bear in mind that some answers require not a little research, and though we endeavor to reply to all, either by letter or in this department, each must take his turn. Special Written Information on matters of personal rather than general interest cannot be expected without remuneration. Scientific American Supplements referred to may be had at the office. Price 10 cents each. Books referred to promptly supplied on receipt of price. Minerals sent for examination should be distinctly marked or labeled.

(2152) E. J. F. writes: 1. Distinguish between ball and cone bearings. A. In one case the journal revolves on conical bearings, in the other case it rolls upon a circle of balls. 2. In dissolving urethane (as used by physicians) I have noticed that the crystals will, after a time, float on the water. They then begin moving about much as if they had life. They jump a small distance, then remain quiet a short time, then move again, and so on. Please explain. A. Surface tension is, we presume, the cause of the phenomenon, as in the case of camphor motions.

(2153) W. R. T. asks: What will bleach ivory after being discolored by age and handling? A. Expose to sun under glass. The direct action of the sun will tend to crack it. Or place on strips of zinc in a vessel, cover with spirits of turpentine, and expose to the sun, not necessarily under glass.

(2154) J. H. writes: 1. My hair has a tendency to curl; will you kindly tell me if there is anything that will help it to curl? A. We can recommend nothing for the purpose. 2. Will you also please inform me which is right? A bets that the National Line of steamers sail under the American flag, and B bets that neither they nor any line of steamers do. A. The National Line of steamers sail under the British flag. No line sails to Europe from this port under the American flag.

(2155) B. L. L. writes: The addition of sodium chloride to a mixture of plaster of Paris and water causes it to set quicker; what is the chemical reaction which takes place? Also when I wish the plaster to set slowly I add potato water (made by boiling potatoes in water), which keeps it soft for some time; how does this affect it? A. There is no reaction in the first case, properly speaking; it is not easy to assign any reason, unless it is the crystallization of the salt. In the second case it is easy to see that the starchy matter of the potatoes might retard the absorption of water,

and might offer a mechanical obstacle to hardening by inclosing with starch and organic matter the molecules of plaster.

(2156) D. E. H. asks for a formula to make the amalgam for the friction pads of an electric machine. A. Melt 8 parts of zinc, add 2 parts tin, place 4 parts heated mercury in a wooden box lined with chalk. Pour in the alloy, cover the box, and shake until cool. Bisulphide of tin is highly recommended as a substitute for amalgam.

(2157) E. V. asks: Which is the more generally adulterated—white or brown sugar? A. We should expect most adulteration in the lower grades of sugar.

(2158) S. T. O.—Lack of hair growth in your case must be due to physical derangement of some kind. Better consult a skilled physician.

(2159) F. G. asks (1) the best and cheapest method of making oxygen gas in quantities of from 50 to 100 cubic feet. A. By heating a mixture of chlorate of potash and binoxide of manganese. A gas of fair purity can be obtained by heating chloride of lime. See SUPPLEMENT, No. 314. The heating is to be done in a retort, with proper precautions, etc. 2. What pressure is required to compress 1 cubic foot of gas into a cylinder 10 inches diameter by 30 inches long? A. About 23 atmospheres. We cannot give the reference asked for. Tessie du Motay's oxygen apparatus consisted of retorts with steam and air plant in which the manganese was heated. Air and steam were alternately passed over the heated mass. The air supplied oxygen, which was given off when the steam was passed over it. The Brin process, described in our SUPPLEMENT, No. 623, is the most promising of the large scale processes.

TO INVENTORS.

An experience of forty years, and the preparation of more than one hundred thousand applications for patents at home and abroad, enable us to understand the laws and practice on both continents, and to possess unequalled facilities for procuring patents everywhere. A synopsis of the patent laws of the United States and all foreign countries may be had on application, and persons contemplating the securing of patents, either at home or abroad, are invited to write to this office for prices, which are low, in accordance with the times and our extensive facilities for conducting the business. Address MUNN & CO., office SCIENTIFIC AMERICAN, 361 Broadway, New York.

INDEX OF INVENTIONS

For which Letters Patent of the United States were Granted

April 15, 1890.

AND EACH BEARING THAT DATE.

[See note at end of list about copies of these patents.]

Abdominal brace and supporter, T. S. Hall.....	425,754
Adjusting device, J. B. Bennett.....	425,486
Air brake system, automatic, H. Guels (r).....	11,070
Alarm. See High and low water alarm.	
Anvil and vise, combined, C. Fisher.....	425,602
Assorting machine, S. B. Smallwood.....	425,705
Automatic sprinkler, J. Clapp.....	425,753
Awning, J. C. Stockton.....	425,962
Axle nut, O. Hansen.....	425,786
Axle nut, J. J. Schadt.....	425,635
Baling press, A. A. Gehrt.....	425,419
Bar. See Fire bar.	
Bath. See Shower bath.	
Batteries, transferring, W. B. Cleveland.....	425,493
Battery. See Galvanic battery. Secondary battery. Thermo-electric battery.	
Bed, W. J. Cristman.....	425,400
Bedstead, folding, A. M. F. Billingslea.....	425,390
Beer, apparatus for treating, C. Hafner.....	425,421
Bell, door, J. Rocheleau.....	425,908
Bells, push button for door, H. F. Eberts.....	425,570
Belt, link driving, J. A. J. Shultz.....	425,704
Belt shifter, G. C. Roberts.....	425,459
Bicycle brake, J. A. Hems.....	425,789
Bicycle pedals, toe clip for, W. G. Rankin.....	425,697
Billboard, J. McKeage.....	425,621
Binders, etc., case for the canvas coverings of, W. M. Wykoff.....	425,646
Blind, T. E. Armitstead.....	425,723
Blind, window, E. Haantsche, Jr.....	425,542
Board. See Billboard.	
Boats, device for securing ferry, F. S. Rudge.....	425,634
Boilers. See Compound boiler. Sectional boiler. Steam boiler. Water jacketed boiler.	
Boiler, J. J. Hogan.....	425,425
Boiler for radiator systems, J. J. Hogan.....	425,946
Boiler heads, machine for flanging, F. L. Kollberg.....	425,484
Boiler with trapped circulation, J. J. Hogan.....	425,944
Boiler with vertical sections, J. J. Hogan.....	425,941
Book and holder, combined account, J. H. Patterson.....	425,455
Boot or shoe stretcher, Gare & Cheetham.....	425,605
Boots, manufacture of India-rubber, C. F. Parker.....	425,454
Boots or shoes, machine for centering soles to, V. F. Lake.....	425,544
Boots or shoes, metallic plate for, Duerden & Cheetham.....	425,758
Bottle case, druggist's, G. A. Rosen.....	425,523
Bottle filling machine, W. H. Comstock.....	425,659
Bottle stopper, J. N. Rhoads.....	425,550
Bottle washing machine, A. Von Schade.....	425,643
Bouquet holder, N. E. Varney.....	425,967
Box. See Deposit box. Fire box. Glass cutting box. Journal box. Match box. Signal box.	
Bowling crease, T. H. Roberts.....	425,551
Brace. See Abdominal brace.	
Braiding and other machines, let-off device for the spools of, Brunner & Hall, Jr.....	425,857
Brake. See Bicycle brake. Car brake.	
Brake, G. Giussani.....	425,670
Brick, burning, J. F. Byers.....	425,536
Buckle, trace, A. Tanquary.....	425,916
Buffer, A. W. Rogers.....	425,632
Buggy seat protector, J. O. Hamaker.....	425,423
Burner. See Hydrocarbon burner. Vapor burner.	
Butter package, H. J. Brine.....	425,564
Button chute, C. J. Brosnan.....	425,928
Button fastening for garments, W. McCabe.....	425,899
Buttonhole pieces, making, M. P. Bray.....	425,533



Cabinet, R. B. Carsley... 425,492
Cabinet, W. I. Ohmer... 425,822 to 425,824
Can. See Metal can.

Emery wheel dressing tool, J. H. Bennett... 425,455
End gate, O. McDowell... 425,620
Engine. See Petroleum engine. Rotary engine
Steam engine.

Leveler, land, J. N. Holland... 425,793
Lifting and pulling machines, coin-controlled test,
Lipe & Lighton... 425,892
Lifting jack, S. F. Hall... 425,765

Register. See Cash register.
Retorts, apparatus for charging, J. H. Du Vivier... 425,538
Rice huller and polisher, W. S. Mallard... 425,631
Rock drill, W. H. Adams... 425,532

**Tubular articles, machine for applying fittings and trimmings on, W. Jackson.....** 425,510  
**Tug, barge, W. E. King.....** 425,678  
**Typewriter, J. Hall.....** 425,876  
**Typewriter, Van Fleet & Graff.....** 425,589  
**Typewriters, copy holder for, J. Chase.....** 425,406  
**Typewriting machine, A. W. Cash.....** 425,931  
**Typewriting machine, J. Hutchison.....** 425,969  
**Vaginal injections, apparatus for removing the waste liquids from, P. A. Adelmann.....** 425,555  
**Valve, P. Conway.....** 425,756  
**Valve, E. W. Luce.....** 425,442  
**Valve for air brakes, automatic, H. Guels (r).....** 11,071  
**Valve, automatic, J. Clapp.....** 425,751, 425,752  
**Valve, rotary balanced, C. R. Hawkins.....** 425,610  
**Valve, slide, E. Leslie.....** 425,681  
**Vapor burner, J. Stubbers.....** 425,639  
**Vat. See Dye vat. Milk vat.....**  
**Vehicle spring, B. C. Cook.....** 425,755  
**Vehicle, two-wheeled, J. Daley.....** 425,506  
**Vehicle, two-wheeled, C. A. Davis.....** 425,410  
**Vehicle wheel, L. H. Donkel.....** 425,934  
**Vehicle wheel, A. C. Hall.....** 425,506  
**Vehicle wheel, Morsman & Higby.....** 425,898  
**Vehicle wheel, S. S. Nuckolls.....** 425,900  
**Velocipede, H. C. Goodrich.....** 425,779  
**Velocipede, C. G. Toense.....** 425,471  
**Velocipede, B. L. Toquet.....** 425,837  
**Vent peg, automatic, C. Wayne.....** 425,530  
**Vignetter, H. J. Lloyd.....** 425,812  
**Violin bow, J. Glass.....** 425,503  
**Violin case, G. A. Holmes.....** 425,427  
**Wagon body and stake holder, E. A. Leinard.....** 425,811  
**Wagon jack, S. Lincoln.....** 425,682  
**Wall paper exhibitor, T. H. Fritz.....** 425,417  
**Walls, binding plate for brick, C. Bischoff.....** 425,854  
**Wardrobe hook, G. W. Tucker.....** 425,919  
**Wash tub pipe connection, B. C. Smith.....** 425,553  
**Washer. See Spring washer.....**  
**Washing machine, G. V. Ballard.....** 425,397  
**Washing machine, D. W. Bowman.....** 425,563  
**Washing machine, L. H. Canfield.....** 425,861  
**Washing machine, C. G. Patterson.....** 425,693  
**Washing machine, Dit Lallemand & Gravel.....** 425,889  
**Watch cases, decorating, E. Leach.....** 425,808  
**Watch cases, machine for decorating, E. Leach.....** 425,807, 425,809  
**Watchmaker's staking and punching tool, E. Rivett.....** 425,522  
**Watch, time striking, J. Robinson.....** 425,582  
**Water closet, Frame & Neff.....** 425,416  
**Water closet tank, P. White.....** 425,921  
**Water conductors, fastener for, W. H. Berger.....** 425,552  
**Water jacketed boiler, J. J. Hogan.....** 425,942  
**Water motor, A. J. Kuehn.....** 425,806  
**Wave power, N. O. Bond.....** 425,927  
**Weather strip, sliding, W. Fitzpatrick.....** 425,414  
**Welding compound, M. Garrison.....** 425,418  
**Wheel. See Car wheel. Fifth wheel. Seeding machine wheel. Vehicle wheel.....**  
**Whiffletree, H. L. Moyer.....** 425,546  
**Windmill, E. B. & O. E. Winger.....** 425,841  
**Wire stretcher, J. W. King.....** 425,805  
**Wool, cotton, etc., machine for opening and mixing, Tindell & Dickerson.....** 425,715  
**Woven pile fabric, Lister & Reixach.....** 425,437  
**Wrench, T. Young.....** 425,647

**DESIGNS.**

**Air compressor case, E. W. Weatherhead.....** 19,765  
**Carriage body, M. Woodhull.....** 19,766  
**Chain bar, watch, W. F. Duryea.....** 19,759  
**Dish, W. G. Walter.....** 19,764  
**Electrical appliances, cabinet for, H. E. Waite.....** 19,763  
**Flame line ring, W. B. Hayden.....** 19,761  
**Handle for sleighs, etc., G. S. Caldwell.....** 19,758  
**Necktie, J. H. Fleisch.....** 19,760  
**Pot or jar, C. W. Meinecke.....** 19,762

**TRADE MARKS.**

**Blood purifier entirely of vegetable origin, S. E. McCormick.....** 17,783  
**Blue, laundry, Heller & Merz Company.....** 17,777  
**Blue, wash, J. De Fremery & Co.....** 17,775  
**Catarrh snuff, F. C. Keith.....** 17,760  
**Cleats, H. Lutmer.....** 17,782  
**Compound for removing stains, grease, etc., from the skin and for other toilet purposes, H. Robbins.....** 17,786  
**Emery wheels and grinding machinery in which they are used, Tanite Company.....** 17,764  
**Food for birds and fowls, natural and prepared, E. R. Durkee & Co.....** 17,772  
**Hair curlers provided with a comb, G. L. Thompson.....** 17,789  
**Horses, body wash in the form of tablets for, Buntin Drug Co.....** 17,768  
**Lobsters, herring, mackerel, and clams, Hatheway & Co.....** 17,776  
**Lotion, healing, W. J. Findley.....** 17,774  
**Medical appliance for the cure of catarrh, W. Northup.....** 17,763  
**Medical compound for liver diseases, J. L. Cooper.....** 17,759  
**Medical remedies, certain named, J. A. W. Fernow.....** 17,773  
**Medicinal compound for headache, sleeplessness, etc., Johnson, Glover & Company.....** 17,781  
**Medicinal tonic in pills, tablets, and suppositories, M. W. Snow.....** 17,788  
**Pantaloon for men and boys, Moses, Sohn & Oppenheimer.....** 17,762  
**Pills, Rogers & Irvin.....** 17,767  
**Stove polish, Buffalo Polish Company.....** 17,767  
**Surgical instruments, Jetter & Scheerer.....** 17,761  
**Teas, mixed, Carlton's Blended Tea Company.....** 17,770  
**Thread, book sewing, Willimantic Linen Company.....** 17,765, 17,766  
**Tobacco, cigars, and cigarettes, smoking and chewing, J. G. Butler & Co.....** 17,769  
**Tobacco, plug chewing and smoking, Hodgkin Bros. & Lunn.....** 17,778  
**Tonic and general stimulant, Mellier Drug Company.....** 17,784  
**Tonic and resolvent, alterative, and expectorant, blood, A. B. C. Chemical Company.....** 17,758  
**Washing compounds, P. Riddle.....** 17,785  
**Weights and similar exercising apparatus, pulley, J. E. Dowd.....** 17,771

A Printed copy of the specification and drawing of any patent in the foregoing list will be furnished from this office for 25 cents. In ordering please state the name and number of the patent desired, and remit to Munn & Co., 361 Broadway, New York.

Canadian Patents may now be obtained by the inventors for any of the inventions named in the foregoing list, provided they are simple, at a cost of \$40 each. If complicated, the cost will be a little more. For full instructions address Munn & Co., 361 Broadway, New York. Other foreign patents may also be obtained.

**Advertisements.**

**Inside Page, each insertion - - - 75 cents a line.**  
**Back Page, each insertion - - - \$1.00 a line.**  
 The above are charges per agate line—about eight words per line. This notice shows the width of the line, and is set in agate type. Engravings may head advertisements at the same rate per agate line, by measurement, as the letter press. Advertisements must be received at publication office as early as Thursday morning to appear in next issue.

**USE ADAMANT WALL PLASTER**  
 It is **Hard, Dense, and Adhesive.** Does not check or crack. It is impervious to wind, water, and disease germs. It dries in a few hours. It can be applied in any kind of weather. It is in general use. Licenses granted for the mixing, using, and selling.  
 Address **ADAMANT MFG. CO.**  
**309 E. Genesee St.,**  
**Syracuse, N. Y.**

**ICE-HOUSE AND REFRIGERATOR.**  
 Directions and Dimensions for construction, with one illustration of cold house for preserving fruit from season to season. The air is kept dry and pure throughout the year at a temperature of from 34° to 36°. Contained in SCIENTIFIC AMERICAN SUPPLEMENT No. 116. Price 10 cents. To be had at this office and of all news-dealers.

**“Star” Foot Lathes** 9x25 in.  
**“L” LATHES** 9x25 in.  
 Screw Cutting Automatic Cross Feed, etc.  
 Catalogue Free of all our Machinery.  
**Seneca Falls Mfg. Co., 695 Water St., Seneca Falls, N. Y.**

**SEBASTIAN, MAY & CO'S**  
 Improved Screw Cutting  
**Foot & Power LATHES** \$60  
 Drill Presses, Chucks, Drills, Dogs, and machinists' and amateurs' outfits. Lathes on trial. Catalogues mailed on application.  
**165 W. 2d St., Cincinnati, O.**

54TH EDITION.—113TH THOUSAND.

**ENGINEERS' POCKET-BOOK**

By CHARLES H. HASWELL.

Mechanics' and Engineers' Pocket-Book of Tables, Rules, and Formulas pertaining to Mechanics, Mathematics, and Physics: including Areas, Squares, Cubes, and Roots, etc.; Logarithms, Hydraulics, Hydrodynamics, Steam and the Steam-Engine, Naval Architecture, Masonry, Steam-Vessels, Mills, etc.; Limes, Mortars, Cements, etc.; Orthography of Technical Words and Terms, etc., etc. 12mo, Pocket-Book Form, pp. 930, \$4.00.

"I cannot find words to express my admiration of the skill and industry displayed in producing the same. To you belongs the honor of having presented to the world a book containing more positive information than was ever before published. I could with justice say more.—Extract from a Letter to the Author from the late Capt. J. Ericsson, the celebrated Engineer."

BY THE SAME AUTHOR.

**MENSURATION AND PRACTICAL GEOMETRY.** Containing Tables of Weights and Measures; Vulgar and Decimal Fractions; Mensuration of Areas, Lines, Surfaces, and Solids; Lengths of Circular Arcs; Areas of Segments and Zones of a Circle; Board and Timber Measure, Centres of Gravity, etc., etc. With a Treatise on the Carpenter's Slide-Rule and Gauging. 12mo, Sheep, pp. 324, 90 cents.

Published by HARPER & BROTHERS, New York.

The above works are for sale by all booksellers, or will be sent by HARPER & BROTHERS, postage prepaid, to any part of the United States, Canada, or Mexico, on receipt of price. HARPER'S NEW CATALOGUE, a descriptive list of over 300 volumes, sent, postpaid, on receipt of Ten Cents.

**PATENT POCKET OILER AND SHEATH**  
 Handiest Oiler in the market. Releases one drop of oil. No waste or leakage. For guns, fishing reels, bicycles, typewriters, fine machines, etc. Send 30 cents for sample.  
**ABSOLUTELY AIR AND OIL TIGHT. BRIDGEPORT GUN IMPLEMENT CO., 17 Maiden Lane, NEW YORK.**

**SPECIAL NOTICE!**  
 We have recently issued a priced Catalogue of **MINING, TUNNELING & QUARRYING MACHINERY.** This is a large volume, profusely illustrated and compiled with the view of placing intelligently before the public **FACTS and FIGURES** relating to Equipment, Cost, and Operation of Mining, Tunneling, and Quarrying Plants. It will be mailed free to any one interested in engaged in **ROCK EXCAVATION or COMPRESSION AIR.** To others it will be sent on receipt of 50 cents in stamps.  
**INGERSOLL-SERGEANT ROCK DRILL CO.**  
 No. 10 Park Place, New York, U. S. A.

**ROCK DRILLS**  
**AIR COMPRESSORS & GENERAL MACHINERY FOR MINING, TUNNELING, QUARRY & RAILROAD WORK.**  
**RAND DRILL CO 23 PARK PLACE NEW YORK**


**\$3 PRINTING PRESS.** Do all your own printing. Save money. Catalogue for two stamps. **Kelsey & Co., Meriden, Conn.**

**ROP HAMMERS**  
**Punching Presses**  
**DIES AND OTHER TOOLS**  
 For the manufacture of all kinds of SHEET METAL GOODS, BRASS FORGINGS, etc.  
**Stiles & Parker Press Co.**  
 Middletown, Conn.  
 Branch Office and Factory, 203, 205 & 207 Center St., N. Y.

**THE CHEMISTRY OF GLASS.—AN** interesting lecture by Prof. Gustav Gehring. The history of glass making. The materials used in the manufacture. The glass furnace and the tools. Properties and uses of glass. Coloring glass. Results in the production of toughened glass. Contained in SCIENTIFIC AMERICAN SUPPLEMENT, No. 737 and 738. Price 10 cents each. To be had at this office and from all news-dealers.

**CATALOGUES FREE TO ANY ADDRESS**  
**GEARS AND PARTS OF MODELS**  
**GOODNOW & WIGHTMAN BOSTON**

**REMINGTON**



**STANDARD TYPEWRITER.**

Gold Medal—Paris Exposition, 1889.  
**Wyckoff, Seamans & Benedict**  
**327 BROADWAY, NEW YORK.**

Fine Taps, Dies, Reamers, Etc.



Lighting and Green River Screw Plates. Bolt Cutters, Hand and Power Drilling Machines, Punching Presses, Tire Benders, Tire Upsetters, and other Labor Saving Tools. Send for Price List.  
**WILEY & RUSSELL MFG. CO., Greenfield, Mass.**

**Steam! Steam!**

Quality Higher, Price Lower.  
 For Strictly Cash, Complete Fixtures except Stack.

2-Horse Eureka Boiler and Engine, - \$135  
 4- " " " " " - 210  
 Other sizes at low prices. Before you buy get our prices.

**B. W. PAYNE & SONS,**  
**Drawer 56. ELMIRA, N. Y.**

**THE PENNA. DIAMOND DRILL & MFG. CO.**  
**BIRDSBORO, PA.,** Builders of High Class Steam Engines, Diamond Drilling and General Machinery. Flour Mill Rolls Ground and Grooved.

NOW READY.

**Experimental Science,**



BY GEO. M. HOPKINS.

740 Pages. 680 Illustrations.

PRICE, by mail, postpaid, . . . \$4.00

SEND for FREE ILLUSTRATED CIRCULAR and Table of Contents.

MUNN & CO., Publishers,

Office of The Scientific American,

361 Broadway, New York.

"Know th Law and Avoid Litigation."

**PAYNE'S LEGAL ADVISER** is a new epitome of the Laws of the States of our Union and those of the General Government of the United States, and will be found invaluable to those who are forced to appeal to the law, as well as to that large class who wish to avoid it. Large 12mo, cloth, 320 pages. Price \$1.50.  
 Post paid on receipt of price.  
**EXCELSIOR PUBLISHING HOUSE,**  
**29 & 31 Beekman Street, New York, N. Y.**

**DROP FORGINGS**  
**FINISHED TOOLS**  
**BILLINGS & SPENCER Co.**  
**HARTFORD CONN.**

**RAILWAY AND STEAM FITTERS' SUPPLIES**

**Rue's Little Giant Injector.**  
**SCREW JACKS, STURTEVANT BLOWERS, &c.**  
**JOHN S. URQUHART, 46 Cortlandt St., N. Y.**

**NUT TAPPING MACHINE.**  
**DURELL'S PATENT.**  
 No. 1 Machine, 900 lb., 7 spindles.  
 " 2 " 1,050 " 7 " "  
 " 3 " 600 " 3 " "  
 Capacity of 7 spindles, 8,000 per 10 hours.  
 Acknowledged to be an indispensable tool. Manufactured by **WM. H. LOCK, Buffalo, N. Y.**

**MARINE ENGINE GOVERNORS.—BY** J. D. Churchill. A place for the wider use of engine governors on sea-going vessels, as a measure of safety. Contained in SCIENTIFIC AMERICAN SUPPLEMENT, No. 734. Price 10 cents. To be had at this office and from all newsdealers.

**STEEL TYPE for TYPEWRITERS,** Stencils, Steel Stamps, Rubber and Metal Type Wheels.  
**New York Stencil Works, Mfrs.**  
 100 Nassau Street, New York.

**STEVENS PATENT IDEAL PENCIL DIVIDERS**  
 No. 69. Sent by mail, postpaid.  
 3 inch only.....\$1.75  
 Our goods excel, for neatness and fine finish, any other make.  
 Ideal and Leader Spring Callipers and Dividers. Ideal Surface Gauges, Depth Gauges, and Fine Machinists' Tools.  
 Illustrated catalogue free to all.  
**J. STEVENS ARMS & TOOL CO.,**  
 P. O. Box 280, Chicopee Falls, Mass.

**HERTZ'S EXPERIMENTS.—A PAPER** by Mr. Joubert, describing some experiments of his own to verify the celebrated ones of Mr. H. Hertz on the intervention of the external medium in electrical phenomena. With 2 figures. Contained in SCIENTIFIC AMERICAN SUPPLEMENT, No. 734. Price 10 cents. To be had at this office and from all newsdealers.

**CHICAGO NICKEL WORKS.**  
**MANUFACTURERS OF**  
**Sohn's Patent Foot Rest,**  
 And Other Metal Specialties.  
 We make a specialty of manufacturing on contract all kinds of metal articles, small machinery, etc. Have the largest nickel-plating works in the west. Obtain our estimate on work and submit meritorious patents for manufacture and sale.  
**CHICAGO NICKEL WORKS, 93 & 95 E. Ohio St. Chicago**

**FOR LINING WALLS WOOL** FREE AND FLOORS TO PREVENT WARMTH ESCAPING AND DEADENING SOUND.  
**USE MINERAL WOOL.**  
**SAMPLES AND CIRCULARS CO.**  
**U. S. MINERAL ST. 200 N. BROADWAY, N. Y. U. S. A.**



Founded by Mathew Carey, 1785.

HENRY CAREY BAIRD & CO. Industrial Publishers, Booksellers, and Importers, 810 Walnut St., Philadelphia, Pa., U. S. A.

SEVENTEENTH TRIENNIAL EXHIBITION - OF THE - MASSACHUSETTS Charitable Mechanic Association OPENS

In their spacious building on Huntington Ave., Boston, OCTOBER 1, 1890. Closing Nov. 29. Manufacturers, Inventors, and Mechanics in every line of Industry, Masters and Students in every department of Science and Art, are invited to send their address.


FOR SALE. C. H. DE LAMATER & CO.

have closed their extensive manufactory at the foot of West 13th Street, New York, disposed of Hot Air Pumping Engine and Steam Pump business to the DE LAMATER IRON WORKS

Lathes, Planers, Drilling, Shaping, Slotting, Boring, Cutting Off, Nut Tapping, Bolt Cutting, and Milling Machines, Gear Cutters, Emery Tool Grinders, Screw Machines, Vises, Lathe and Planer Tools, Drills, Taps, And a variety of Small Tools, Boiler Punching and Shearing Machines, with lot of Small Tools, Anvils, Sledges, Tongs, Blocks, Rope, Bolts, Nuts, Washers, Packing, Pipe, Fittings, Brass Valves, Bar Iron and Steel, Steam Hammers, and three Rider Cut-off Engines.

Perfectly Non-Poisonous, Odorless, Sanitary.

It slowly dissolves in water, making a constant Disinfectant for water-closets, urinals, sinks, drains, sewers, cesspools, privies, vaults, stables, kennels, bilge-water, spittoons, sinks, and every place that needs Disinfecting.



THE BAILEY DISINFECTANT CO., Sole Manufacturers and Patentees, Boylston Building, Boylston St., Boston, Mass.

TYPEWRITERS ALL MAKES, NEW & SECOND HAND - BOUGHT, SOLD AND EXCHANGED. NATIONAL TYPEWRITER EXCHANGE ANYWHERE IN THE U.S. 200 LASALLE ST. CHICAGO.

BARNES' PAT. FOOT POWER MACHINERY. I feel so highly pleased with your Velocipede Foot Power with seat, that I wish to add my testimony to its superiority.

The First Prize of a Gold Medal awarded the "Hammond" at the Paris Exposition. THE HAMMOND TYPEWRITER CO. 447, 449 East 52d Street, NEW YORK, U. S. A.

PATENTEES having some Novel Invention in Light Hardware or Machinery which they desire to have manufactured on royalty or to sell outright are requested to address the undersigned, who has a well equipped machine shop.

Hoskins' Patent Hydro-Carbon BLOW-PIPE AND ASSAY FURNACES. No dust, no ashes, Cheap, effective, economical, portable, and automatic.

Barrel, Keg, Hogshead AND STAVE MACHINERY. Over 25 varieties manufactured by E. & B. Holmes, BUFFALO, N. Y.

Moss Engraving Co. 535 PEARL ST. NEW YORK. ENGRAVINGS FOR BOOKS, NEWSPAPERS AND CIRCULARS. SEND GREEN STAMP FOR CIRCULAR - SEND PHOTOGRAPH, DRAWING OR PRINT FOR ESTIMATE.

Shipman Automatic Steam Engine Oil or Natural Gas Fuel. 1, 2, 4, 6, and 8 Horse Power Single, 3, 6, and 16 Horse Power Compound. Over 2,500 in Actual Use.

The Manufacturers of the United States For Domestic and Foreign Trade.

Containing Names and Addresses of 100,000 Manufacturers of 20,000 Articles in 178 Classified Trades in the United States. A complete Reference Book for buyers and sellers in all trades, showing where any article of American manufacture can be purchased direct.

SPYGLASSES & ASTRONOMICAL TELESCOPES. ACHROMATIC OBJECTIVES, EQUATORIAL STANDS, TRANSITS, CLOCKS, EYEPIECES & LENSES, CHRONOGRAPHS, &c.

Penberthy Automatic Injector. Cost less than others and do equal work. Lift 20 feet and work from head as well.

WORKING MODELS and Experimental Work to Order. Inventions developed. A accurate and intricate work a specialty. N. ERLANDSEN, 107 Rivington St., N. Y.

2nd MACHINERY. THE BEST LIME KILN KNOWN or no pay. C. D. PAGE, Rochester, N. Y.

WORKING MODELS & LIGHT MACHINERY. INVENTIONS DEVELOPED. Send for Model Circular. Jones Bros. E. Co., Cin'ti, O.

A PRACTICAL TEACHER. Payne's Business Educator. An encyclopedia of the knowledge necessary to the conduct of business. Model Business Letters and Answers; Lessons in Penmanship; Interest Tables; Rules of Order for Deliberative Assemblies and Debating Societies; Tables of Weights and Measures, Standard and the Metric System; Lessons in Typewriting; Dictionary of Mercantile Terms; Interest Laws of the United States; Value of Foreign Gold and Silver Coins in the United States; Rules of Punctuation; Marks of Accent; Dictionary of Synonyms, etc., etc., making in all the most complete self-educator published. Containing 608 pages, bound in extra cloth. Price \$2.00. Post paid on receipt of price. Excelsior Publishing House, 29 & 31 Beekman Street, New York, N. Y.

NATIONAL STEEL TUBE CLEANER

Cheap Printing. Do it yourself. Circular press \$8. Size for small newspapers, \$14. Everything easy, printed rules. Send two stamps for Catalogue to factory. KELSEY & CO., Meriden, Conn.

FAMILY ICE MACHINE. Ice in few minutes. Price, \$10 to \$185. Circular. L. Dermigny, 126 West 25th Street, New York.

THE EAGLE THE EASIEST RUNNING BICYCLE IN THE WORLD. Speed, Comfort and Safety. AGENTS WANTED. Large Illustrated Catalogue sent Free to any Address. THE EAGLE BICYCLE MFG. CO., STAMFORD, CONN.

PHOTOGRAPHY MADE EASY. The Amateur Photographers Handbook, by Arthur Hope. The Latest and best work on the subject, thoroughly practical and clear. The book of all others for the amateur and professional. New processes, hitherto unpublished. Writes an eminent photographer, "Your chapter on Exposures is unique." Beautiful illustrations. Send for descriptive circular. Paper covers, 75 cts. Cloth, \$1.25. By mail on receipt of price. THE JOHN WILKINSON CO., Publishers, 55 State Street, Chicago.

DEAFNESS & HEAD NOISES CURED BY PECK'S INVISIBLE TUBULAR EAR CUSHIONS. Whispers heard. Comfortable. Successful where all Remedies FAIL. Ills. book & proofs free. Address F. HISCOP, 863 Broadway, New York.

CELEBRATED SUTTON RING PACKING. POSITIVELY ANTI-FRICTION. SPECIALLY ENDORSED FOR HIGH SPEED ENGINES. PIONEER RUBBER PACKING. SEND FOR SAMPLE PACKAGE AND PARTICULARS TO ERIE RUBBER CO. ERIE PA. U.S.A.

PULLEYS HANGERS, FRICTION CLUTCHES. PROGRESS MACHINE WORKS, A. & F. BROWN, 44 Park Place, N. Y.

RANKS THE HIGHEST. Endorsed by the best Engineers. CHALMERS-SPENCE CO. Office, 59 Liberty Street, Works, 419-425 E. Eighth St., New York

The most successful Lubricator for Loose Pulleys in use. VAN DUZEN'S PATENT LOOSE PULLEY OILER. Highly recommended by those who have used them for the past two years. Prices very reasonable. Every user of machinery should have our "Catalogue No. 55" sent free. VAN DUZEN & TIFT, Cincinnati O.

A NEW CATALOGUE OF VALUABLE PAPERS. Contained in SCIENTIFIC AMERICAN SUPPLEMENT, sent free of charge to any address. MUNN & CO., 361 Broadway, New York.

OUR MAGIC LANTERNS WITH OIL LAMPS HAVE NO EQUAL VIEWS OF ALL SUBJECTS. EASTERN PRICES GUARANTEED. L. MANASSE 88 MADISON ST. CHICAGO ILL.

ASBESTOS Fire Felt Coverings, Packings, Sneathings, &c. The CHALMERS-SPENCE CO., Mfrs. 419-425 E. Eighth Street, New York.

PLAYS. Dialogues, Tableaux, Speakers, for School, Club & Parlor. Best out. Catalogue free. T. S. DENISON, Chicago, Ill.

AGENTS WANTED by an old reliable firm: large profits quick sales. SAMPLE FREE. A rare opportunity. Geo. A. Scott, 842 Broadway, N. Y.

E-HOUSE AND COLD ROOM. BY R. C. Hatfield. With directions for construction. Four engravings. Contained in SCIENTIFIC AMERICAN SUPPLEMENT, 59. Price 10 cents. To be had at this office and of all newsdealers.

RATS, MICE, OR VERMIN will not pass through it. IN YOUR WALLS OR FLOORS. Sample Free. WESTERN GENERAL WOOL CO., Cleveland, Ohio.

G. G. TURRI & CO., International Patent Agents. Melbourne, Victoria, will supply the profession with blank forms and full instructions for all Australasian Colonies. Latest alterations embodied. We accept no instructions for obtaining Patents from inventors direct.

FOR SALE. Patent No. 424,731, Self-Oiling Car Axle. For further particulars, apply to R. P. Sholl, Bartonville, Ill.

WANTED for cash, Second-hand Corliss Engine, about 12x30, warranted in perfect order. H. Houghton, 127 West Ave., Hunter's Point, L. I., N. Y.

INVENTORS! - We make anything you want from a Screw to Complete Working Model. Inventions perfected, details worked out, drawings made. Repairs. Circulars sent. A. J. WEED & CO., 92 Fulton St., N. Y.

The Scientific American PUBLICATIONS FOR 1890.

The prices of the different publications in the United States, Canada, and Mexico are as follows: RATES BY MAIL. The Scientific American (weekly) one year \$3.00. The Scientific American Supplement (weekly), one year 5.00. The Scientific American, Spanish Edition (monthly) one year 3.00. The Scientific American, Architects and Builders Edition (monthly), one year 2.50. COMBINED RATES. The Scientific American and Supplement, \$7.00. The Scientific American and Architects and Builders Edition, 5.00. The Scientific American, Supplement, and Architects and Builders Edition, 9.00. Proportionate Rates for Six Months. This includes postage, which we pay. Remit by postal or express money order, or draft to order of MUNN & CO., 361 Broadway, New York.

LITTLE GIANT WATER WHEEL. Cheapest and best wheel in the market. Send for catalogue and price list. MUNSON BROS., UTICA, N. Y., U. S. A.

HOME-MADE INCUBATOR. - PRACTICAL directions for the manufacture of an effective incubator that has been carefully tested and found to perform all that may be reasonably expected; with directions for operating. With 4 figures. Contained in SCIENTIFIC AMERICAN SUPPLEMENT, NO. 620. Price 10 cents. To be had at this office and from all newsdealers.

PERFECT NEWSPAPER FILE. The Koch Patent File, for preserving newspapers, Magazines, and pamphlets, has been recently improved and price reduced. Subscribers to the SCIENTIFIC AMERICAN and SCIENTIFIC AMERICAN SUPPLEMENT can be supplied for the low price of \$1.50 by mail, or \$1.25 at the office of this paper. Heavy board sides; inscription "SCIENTIFIC AMERICAN" in gilt. Necessary for every one who wishes to preserve the paper. Address MUNN & CO., Publishers SCIENTIFIC AMERICAN.

THE BACKUS WATER MOTOR. THE BACKUS EXHAUST FAN. With or without Governor. Supplies from hydrant pressure the cheapest power known. Invaluable for blowing church organs, running printing presses, sewing machines, lathes, saws, coffee mills, fans, sausage cutters, elevators, and all machinery requiring light power. No firing, no fuel, no ashes, no repairs, noiseless and compact. No extra insurance. Always ready. Supplies from 14 to 10 H. P. Interchangeable jets and improved in every detail. References in all parts of the country. Send for special circulars to the Backus Water Motor Co., Newark, N. J.

ELECTRICAL DICTIONARY. Just Published! A Dictionary of Electrical Words, Terms, and Phrases. By Prof. E. J. Houston. 655 pages, 397 illustrations. Cloth. Price, postage prepaid, \$2.50. This new and important work meets a universally-felt and growing need, by giving in plain and simple language a clear, concise definition of the exact meaning of the many words, terms, and phrases embraced in the Terminology of Electricity, followed by a general statement of the principles of electrical science on which such definitions are founded.

There is no work relating to Electricity that we do not either publish or sell. Copies of any Electrical book or books will be promptly mailed to any address in the world, postage prepaid, on receipt of price. Information regarding Electrical Books cheerfully furnished on application. We carry a full line. If you live in or near New York, call and examine at your leisure any Electrical books you desire, and we shall gladly assist you if we can. Our complete classified catalogue of Electrical Books mailed free to any address on application.

Avoiding abstruse technicalities, THE ELECTRICAL WORLD seeks to keep its readers informed of every event of importance, every new discovery, invention, application, and theory in which Electricity plays a part. No one who desires to keep up with the wonderful activity in Electrical discovery and invention can afford to be without it. Samples free. The paper may be ordered regularly of any newsdealer in the U. S. or Canada, at a cost of 10 cents a week. Any postmaster or newsdealer will take your subscription, or remit direct to the Publishers, THE W. J. JOHNSTON CO., Ltd., 167-177 Times Building, New York.

ELECTRICAL WORLD

Advertisements.

Inside Page, each insertion - - - 75 cents a line. Back Page, each insertion - - - \$1.00 a line.


The above are charges per agate line—about eight words per line. This notice shows the width of the line, and is set in agate type. Engravings may head advertisements at the same rate per agate line, by measurement, as the letter press. Advertisements must be received at publication office as early as Thursday morning to appear in next issue.

Victor Bicycles!



For pleasure, business, recreation, and for anything you could use a bicycle for. VICTORS ARE BEST! Send for catalogue. Overman Wheel Co., Makers, Chicopee Falls, Mass.

THE PHONOGRAPH.—A DETAILED description of the new and improved form of the phonograph just brought out by Edison. With 8 engravings. Contained in SCIENTIFIC AMERICAN SUPPLEMENT, No. 692. Price 10 cents. To be had at this office and from all newsdealers.



COMPTOMETER

All Arithmetical problems are solved rapidly and accurately by the Comptometer. It is operated by keys like the typewriter and gives entire relief from mental strain. It is the only machine on which addition can be performed faster than with the pencil, and is adapted to all commercial and scientific computations.

"We feel that we could not do without it, without causing us great inconvenience."—GEO. L. CHASE, President Hartford Fire Insurance Co.

"It not only does the calculations many times quicker, but it also saves time in not having to write down the numbers for calculation."—DR. DANIEL DRAPE, Ph.D., Director Meteorological Observatory, Central Park, New York

"I find it invaluable in adding up long columns of figures, and can safely say that I can do twice as much work with the machine."—F. W. SOUTS, Registry Clerk, North Chicago Street Ry. Co.

"Have found it a great help for accurate and rapid work in multiplication."—W. H. HITT, Chicago Copper Refining Co.

"This bank purchased a Comptometer of the Felt & Tarrant Mfg. Co., and have used it for the past year in the work of adding long columns of figures. It has proved a valuable help, and we would not like to be without it."—W. A. SHAW, Cashier of the Merchants' and Manufacturers' National Bank, Pittsburgh, Pa.

Send for circular. FELT & TARRANT MFG. CO., 52 Illinois Street, Chicago.



JENKINS BROS. VALVES! JENKINS BROS., 71 John St., N. Y.; 105 Milk St., Boston; 21 North 5th St., Phila.; 31 Dearborn St., Chicago.

NEW KODAKS




"You press the button, we do the rest."

Seven New Styles and Sizes ALL LOADED WITH Transparent Films.

For sale by all Photo. Stock Dealers. THE EASTMAN COMPANY, ROCHESTER, N. Y. Send for Catalogue.

GATES ROCK & ORE BREAKER



Capacity up to 150 yards per hour. Has produced more ballast, road metal, and broken more ore than all other Breakers combined. Send for Catalogues. GATES IRON WORKS, 50 C So. Clinton St., CHICAGO, 215 Franklin St., Boston, Mass.

Scientific Book Catalogue

RECENTLY PUBLISHED. Our new catalogue containing over 100 pages, including works on more than fifty different subjects. Will be mailed free to any address on application. MUNN & Co., Publishers Scientific American, 361 Broadway, New York.




NICKEL AND ELECTRO-PLATING APPARATUS AND MATERIAL HANSON, VAN WINKLE & CO. NEWARK, N. J. 92 LIBERTY ST. N. Y.

PATENTS!

MESSRS. MUNN & CO., in connection with the publication of the SCIENTIFIC AMERICAN, continue to examine improvements, and to act as Solicitors of Patents for Inventors. In this line of business they have had forty-one years' experience, and now have unexcelled facilities for the preparation of Patent Drawings, Specifications, and the prosecution of Applications for Patents in the United States, Canada, and Foreign Countries. Messrs. Munn & Co. also attend to the preparation of Caveats, Copyrights for Books, Labels, Reissues, Assignments, and Reports on Infringements of Patents. All business entrusted to them is done with special care and promptness, on very reasonable terms. A pamphlet sent free of charge, on application, containing full information about Patents and how to procure them; directions concerning Labels, Copyrights, Designs, Patents, Appeals, Reissues, Infringements, Assignments, Rejected Cases. Hints on the Sale of Patents, etc. We also send, free of charge, a Synopsis of Foreign Patent Laws, showing the cost and method of securing patents in all the principal countries of the world. MUNN & Co., Solicitors of Patents, BRANCH OFFICES—No. 627 F Street, Pacific Building, near 7th Street, Washington, D. C.

THE BRIDGEPORT WOOD FINISHING CO. C. M. BREINIG, AGENT, PRINCIPAL OFFICE AT MANUFACTORY NEW MILFORD, CONN. NEW YORK OFFICE, 240 PEARL ST. CHICAGO OFFICE & WAREHOUSE 271 EAST RANDOLPH ST. MANUFACTURERS OF WHEELERS PATENT WOOD MILLER. BREINIG'S LITHOGEN SILICATE PAINT LITHOGEN PRIMER, WOOD STAINS SILEX FLINT AND FELDSPAR. PAMPHLET GIVING DIRECTIONS FOR FINISHING HARD WOOD FREE TO ANY ADDRESS.

THE TEACHING OF SCIENCE.—Report of the British Association Committee appointed for the purpose of inquiring into and reporting upon the present methods of teaching chemistry. Contained in SCIENTIFIC AMERICAN SUPPLEMENT, Nos. 734 and 735. Price ten cents each. To be had at this office and from all newsdealers.



"COLUMBIAS" HIGHEST GRADE ONLY.

Catalogue Free. POPE MFG. CO. BRANCH HOUSES: 77 Franklin St., BOSTON. 12 Warren St., NEW YORK. 291 Wabash Ave., CHICAGO.

THE ONLY PRACTICAL LOW-PRICED \$15 TYPEWRITER

Catalogue free. Address Typewriter Department, POPE MFG. CO., Boston, New York, Chicago.

THE COPYING PAD.—HOW TO MAKE and how to use; with an engraving. Practical directions how to prepare the gelatine pad, and also the aniline ink by which the copies are made; how to apply the written letter to the pad; how to take off copies of the letter. Contained in SCIENTIFIC AMERICAN SUPPLEMENT, No. 438. Price 10 cents. For sale at this office and by all newsdealers in all parts of the country.

THE FRED'K CRANE CHEMICAL CO. SHORT HILLS, N. J. - BOX 91A - ZAPONS, BRUSH & DIP, LACQUERS, VARNISH, SHELLACS, BLACKS, BRILLIANT & DEAD, JAPANS, AIR DRYING, ENAMELS, TRANSPARENT, FOR METAL AND WOOD, PROOF AGAINST ACIDS AND ALKALIES. —WRITE FOR CATALOGUE—

FORGING AND WELDING BY PETROLEUM AIR BLAST FIRES. All Oil Below Burners.

REPRESENTED BY Wm. Pickett, Son & Co., 170 Lake St., Chicago; and St. Louis, W. S. Collins, 171 B'way, New York; Chilton Jones, Gannaque, Can.; G. M. Smith, Los Angeles, Cal.; Alden Speare's Sons & Co., 3 Central Wharf, Boston; Kalamazoo Spring & Axle Co., Kalamazoo, Mich. \*We will replace in Stock or Mutual Companies any Insurance canceled on account of using this system when installed according to our plans.



THE AERATED FUEL COMPANY, Springfield, Mass.

CUTLER DESK. BEST IN THE WORLD. A CUTLER & SON, BUFFALO, N. Y., U.S.A.

ALUMINUM.—DESCRIPTION OF THE method of manufacturing this metal from cryolite as practiced at the Alliance Aluminum Works at Walsend. With 3 figures. Contained in SCIENTIFIC AMERICAN SUPPLEMENT, No. 731. Price 10 cents. To be had at this office and from all newsdealers.

THE STANDARD H.W. JOHNS' ASBESTOS BOILER COVERINGS. H.W. JOHNS' MFG. CO. 87 MAIDEN LANE, NEW YORK. PATENTED CHICAGO, PHILADELPHIA, LONDON.

THE AMERICAN BELL TELEPHONE CO. 95 MILK ST., BOSTON, MASS.

This Company owns the Letters Patent granted to Alexander Graham Bell, March 7th, 1876, No. 174,465, and January 30th, 1877, No. 186,787.


The transmission of Speech by all known forms of Electric Speaking Telephones infringes the right secured to this Company by the above patents, and renders each individual user of telephones not furnished by it or its licensees responsible for such unlawful use, and all the consequences thereof, and liable to suit therefor.

A Substitute for Coal or Coke. 100 Gallons of Oil against 2,400 Pounds of Coal. A SYSTEM FOR BURNING CRUDE PETROLEUM. The best practical results obtained by the manufacturers of Steel, Drop Forgings, Brass Works, Bolt and Nut Works, and many other branches of commercial product. We invite proposals and will give estimates for the alteration or construction of works under our system. THE STANDARD OIL FUEL BURNER CO., Fort Plain, N. Y.

SHIPMAN AUTOMATIC STEAM ENGINES. OVER 2500 IN USE. MARINE AND STATIONARY. SAFE, RELIABLE, ECONOMICAL, REQUIRING NO SKILLED ENGINEER. SEND 4 CENTS FOR ILLUSTRATED CATALOGUE. HAWTHORN & CO. 12 BORTLAND ST. NEW YORK.

A Voice from the Golden State. Engine was shipped to these parties with instructions for setting up and operating. SANTA PAULA, Cal., Oct. 29, 1889. CHARTER GAS ENGINE CO., Sterling, Ill. GENTS:—In reply to your enquiries in letter of the 23d. We are running with the No. 3 Charter Engine purchased of you, a Lathe, a Blower for our Blacksmith Shop, Bolt Cutter, sometimes a Punch and Shears for tank and boiler iron. It will run the whole shop with ease, where we formerly had a 12 H. P. engine and 20 H. P. boiler. Our expense for September was about \$33.00, as against \$71.80 for fuel alone, for July, say nothing about the engineer and the repairs on boiler, which is no small item when water is bad. Yours respectfully. HARDISON & STEWART OIL CO.

VAN DUZEN GAS & GASOLINE ENGINE



OPERATED WITH COAL AND OTHER MANUFACTURED GASES AND GASOLINE. RELIABLE AND ECONOMICAL. Fully Warranted VAN DUZEN Gas & Gasoline Engine Co. 53 E. 2d St., Cincinnati, O.

OUR MOTOR. PERFECT POWER For Any Purpose.



CHICAGO WATER MOTOR CO. 88 Lake Street, Chicago, Ill.

SYRACUSE MALLEABLE IRON WORKS W. B. BURNS PROPRIETOR

OTIS ELEVATORS THE STANDARD OF THE WORLD

For all kinds of PASSENGER and FREIGHT Elevator Service.

OTIS BROTHERS & CO. General Offices, NEW YORK.

GRAVES ELEVATORS. PASSENGER & FREIGHT S. GRAVES & SON ROCHESTER N. Y. NEW YORK, BOSTON, ST. LOUIS, DETROIT.

POP SAFETY VALVE WATER RELIEF VALVE IMPROVED STEAM GAGE STEAM ENGINE INDICATOR

Single Bell Chime Whistle, and all instruments used in connection with Steam, Air and Water. Sole Agents for Clark's Lanen Fire Hose. NEW YORK. CROSBY STEAM GAGE & VALVE CO. 98 Oliver St. Boston, Mass.

NOTES ON ESSENTIAL OILS.—A valuable paper descriptive of a number of oils derived from plants, with their characteristics, tests, etc. Contained in SCIENTIFIC AMERICAN SUPPLEMENT, No. 732. Price 10 cents. To be had at this office and from all newsdealers.

TOOL AGENTS WANTED in every SHOP in the United States. Send 10c for Catalogue. Stationery &c. THE FINEST OF MECHANICAL TOOLS A SPECIALTY. C. B. JAMES, 93 LAKE ST. CHICAGO.

THE Scientific American ESTABLISHED 1846.

The Most Popular Scientific Paper in the World.

Only \$3.00 a Year, including Postage. Weekly. 52 Numbers a Year.

This widely circulated and splendidly illustrated paper is published weekly. Every number contains sixteen pages of useful information and a large number of original engravings of new inventions and discoveries, representing Engineering Works, Steam Machinery, New Inventions, Novelties in Mechanics, Manufactures, Chemistry, Electricity, Te engraving, Photography, Architecture, Agriculture, Horticulture, Natural History, etc. Complete List of Patents each week.

Terms of Subscription.—One copy of the SCIENTIFIC AMERICAN will be sent for one year—52 numbers—postage prepaid, to any subscriber in the United States, Canada or Mexico, on receipt of three dollars by the publishers; six months, \$1.50; three months, \$1.00.

Clubs.—Special rates for several names, and to Post Masters. Write for particulars.

The safest way to remit is by Postal Order, Draft, or Express Money Order. Money carefully placed inside of envelopes, securely sealed, and correctly addressed, seldom goes astray, but is at the sender's risk. Address all letters and make all orders, drafts, etc., payable to

MUNN & CO., 361 Broadway, New York.

THE Scientific American Supplement.

This is a separate and distinct publication from THE SCIENTIFIC AMERICAN, but is uniform therewith in size, every number containing sixteen large pages full of engravings, many of which are taken from foreign papers, and accompanied with translated descriptions. THE SCIENTIFIC AMERICAN SUPPLEMENT is published weekly, and includes a very wide range of contents. It presents the most recent papers by eminent writers in all the principal departments of Science and the Useful Arts, embracing Biology, Geology, Mineralogy, Natural History, Geography, Archaeology, Astronomy, Chemistry, Electricity, Light, Heat, Mechanical Engineering, Steam and Railway Engineering, Mining, Ship Building, Marine Engineering, Photography, Technology, Manufacturing Industries, Sanitary Engineering, Agriculture, Horticulture, Domestic Economy, Biography, Medicine, etc. A vast amount of fresh and valuable information obtainable in no other publication.

The most important Engineering Works, Mechanisms, and Manufactures at home and abroad are illustrated and described in the SUPPLEMENT.

Price for the SUPPLEMENT for the United States and Canada, \$5.00 a year, or one copy of the SCIENTIFIC AMERICAN and one copy of the SUPPLEMENT, both mailed for one year for \$7.00. Single copies 10 cents. Address and remit by postal order, express money order, or check, MUNN & Co., 361 Broadway, N. Y., Publishers SCIENTIFIC AMERICAN.

Building Edition.

THE SCIENTIFIC AMERICAN ARCHITECTS' AND BUILDERS' EDITION is issued monthly. \$2.50 a year. Single copies, 25 cents. Forty large quarto pages, equal to about two hundred ordinary book pages; forming a large and splendid Magazine of Architecture, richly adorned with elegant plates in colors, and with other fine engravings; illustrating the most interesting examples of modern Architectural Construction and allied subjects.

A special feature is the presentation in each number of a variety of the latest and best plans for private residences, city and country, including those of very moderate cost as well as the more expensive. Drawings in perspective and in color are given, together with full Plans, Specifications, Sheets of Details, Estimates, etc.

The elegance and cheapness of this magnificent work have won for it the Largest Circulation of any Architectural publication in the world. Sold by all newsdealers. \$2.50 a year. Remit to

MUNN & CO., Publishers, 361 Broadway, New York.

PRINTING INKS. THE "Scientific American" is printed with CHAS. T. HENU JOHNSON & CO.'S INK, Tenth and Lombard Sts., Phila., and 47 Rose St., opp. Duane St., N. Y.